



US00D536545S

(12) **United States Design Patent**  
**Young**

(10) **Patent No.:** **US D536,545 S**

(45) **Date of Patent:** **\*\* Feb. 13, 2007**

(54) **SEAT WITH ARMRESTS OF A TRUCK VEHICLE**

(75) Inventor: **Bryan Young**, Fort Wayne, IN (US)

(73) Assignee: **International Truck and Engine Corporation Canada**, Warrenville, IL (US)

(\*\*) Term: **14 Years**

(21) Appl. No.: **29/233,162**

(22) Filed: **Jun. 28, 2005**

(51) **LOC (8) Cl.** ..... **06-01**

(52) **U.S. Cl.** ..... **D6/356**

(58) **Field of Classification Search** ..... D6/334-336, D6/356, 367, 368, 374, 375, 500-502; 297/232, 297/391, 284.9, 411.3, 452.24, 452.25, 452.26, 297/452.29, 452.34, 452.35, 354.1

See application file for complete search history.

(56) **References Cited**

**U.S. PATENT DOCUMENTS**

D242,508 S	*	11/1976	Skyer et al.	.....	D6/356
D257,748 S	*	1/1981	Smith	.....	D6/356
D264,774 S	*	6/1982	McGirk et al.	.....	D6/356
D280,470 S	*	9/1985	Higgins	.....	D6/356
D280,471 S	*	9/1985	Higgins	.....	D6/356
D281,472 S	*	11/1985	Soederberg	.....	D6/356
D283,089 S	*	3/1986	McArdle	.....	D6/367
4,707,027 A	*	11/1987	Horvath et al.	.....	297/284.9
D315,255 S	*	3/1991	Beermann	.....	D6/356
D326,959 S	*	6/1992	VanDuser et al.	.....	D6/356
D394,756 S	*	6/1998	Gryp et al.	.....	D6/356
D426,392 S	*	6/2000	Ott et al.	.....	D6/356
D480,570 S	*	10/2003	Gryp et al.	.....	D6/356

\* cited by examiner

*Primary Examiner*—Mimosa De

(74) *Attorney, Agent, or Firm*—Jeffrey P. Calfa; Gerald W. Askew; Dennis K. Sullivan

(57) **CLAIM**

The ornamental design for a seat with armrests of a truck vehicle, as shown and described.

**DESCRIPTION**

FIG. 1 is a right, front perspective view of a seat of a truck showing my new design, said seat having the armrests rotated to a down position;

FIG. 2 is a right, front perspective view of a seat of a truck showing my new design, said seat having the armrests rotated to an up position;

FIG. 3 is a right view of a seat of a truck showing my new design, said seat having the armrests rotated to a down position;

FIG. 4 is a right view of a seat of a truck showing my new design, said seat having the armrests rotated to an up position;

FIG. 5 is a front view of a seat of a truck showing my new design, said seat having the armrests rotated to a down position;

FIG. 6 is a front view of a seat of a truck showing my new design, said seat having the armrests rotated to an up position;



FIG. 7 is a top down view of a seat of a truck showing my new design, said seat having the armrests rotated to a down position;

FIG. 8 is a top down view of a seat of a truck showing my new design, said seat having the armrests rotated to an up position;

FIG. 9 is a rear view of a seat of a truck showing my new design, said seat having the armrests rotated to a down position; and,

FIG. 10 is a rear view of a seat of a truck showing my new design, said seat having the armrests rotated to an up position.

**1 Claim, 5 Drawing Sheets**






FIG. 1




FIG. 2




FIG. 3






FIG. 4



**FIG. 5**



**FIG. 6**






FIG. 7






FIG. 8



**FIG. 9**



**FIG. 10**