



US00D537406S

(12) **United States Design Patent**
Reim

(10) **Patent No.:** **US D537,406 S**

(45) **Date of Patent:** **** Feb. 27, 2007**

(54) **TIRE TREAD**

(75) Inventor: **Kevin Ray Reim**, Simpsonville, SC (US)

(73) Assignee: **Michelin Recherche et Technique S.A.**, Granges-Paccot (CH)

(**) Term: **14 Years**

(21) Appl. No.: **29/253,181**

(22) Filed: **Feb. 2, 2006**

(51) **LOC (8) Cl.** **12-15**

(52) **U.S. Cl.** **D12/555; D12/590**

(58) **Field of Classification Search** D12/551, D12/552, 553, 554, 555, 556, 583, 585, 586, D12/587, 588, 589, 590, 591, 600; 152/209.1, 152/209.9, 209.25, 209.28

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

4,424,843	A	*	1/1984	Fontaine et al.	152/209.1
4,424,845	A	*	1/1984	Baus et al.	152/209.1
D349,873	S	*	8/1994	Shibata et al.	D12/588
D423,418	S		4/2000	Meslot et al.	D12/141
D431,503	S		10/2000	Cinquin	D12/147
D432,957	S		10/2000	Ricquet	D12/141
D449,816	S		10/2001	Hutz	D12/564
D475,344	S	*	6/2003	Tsubono	D12/603
D488,771	S	*	4/2004	Villamizar	D12/590

OTHER PUBLICATIONS

Kumho Solus KH15 Tire, 2004 Tread Design Guide, Jan. 2004, p. 34. 2/4.*

Riken Raptor H4 Tire, 2004 Tread Design Guide, Jan. 2004, p. 50. 3/5.*

Daytona SR Tire with Uni-T Tire, 2 pages, Found on World Wide Web at: http://www.bridgestone-usa.com/media/da_tires.asp.*

Tread Design Guide, 1996, p. 17, CONTINENTAL Conti 4-Season Contact.

Tread Design Guide, 1996, p. 45, MARSHAL 771.

Tread Design Guide, 1996, p. 59, PIRELLI P7000 Super-sport.

Tread Design Guide, 1996, p. 62, RIKEN Classic MR-GT.

Tread Design Guide, 2004, p. 19, DELTA Esteem XLE.

Tread Design Guide, 2004, p. 35, KUMHO Ecsta DX.

Tread Design Guide, 2004, p. 64, YOKOHAMA AVS Winter.

* cited by examiner

Primary Examiner—Robert M. Spear

(74) *Attorney, Agent, or Firm*—E. Martin Remick; Adam Arnold; Frank J. Campigotto

(57) **CLAIM**

The ornamental design for a tire tread, a shown and described.

DESCRIPTION



FIG. 1 is a perspective view of a tire tread showing my new design, it being understood that the non-directional tread pattern repeats circumferentially throughout the outer circumference and shoulder of a tire, the opposite side perspective view being an identical image thereto;

FIG. 2 is an enlarged fragmentary front elevation view of the tire tread thereof of FIG. 1; and,

FIG. 3 is a perspective view of a tire tread showing a second embodiment of my new design, it being understood that the directional tread pattern repeats circumferentially throughout the outer circumference and shoulder of a tire, the opposite side perspective view being an inverted image thereto.

In the drawings, the dark stippled surface shading represents the recessed groove portions of the tire tread having a depth as best illustrated along the right edge of FIGS. 1 and 3. The broken line disclosure of the tire sidewall and inner bead is for illustrative purposes only and forms no part of the claimed design.

1 Claim, 3 Drawing Sheets






Fig. 1




Fig. 2




Fig. 3