



US00D538431S

(12) **United States Design Patent**
Botha

(10) **Patent No.:** **US D538,431 S**
(45) **Date of Patent:** **** Mar. 13, 2007**

(54) **JOINT PROSTHESIS COMPONENT**

(75) Inventor: **Pieter Johannes Botha**, Krugersdorp
(ZA)

(73) Assignee: **Arthrosearch (PTY) Ltd.** (ZA)

(**) Term: **14 Years**

(21) Appl. No.: **29/225,337**

(22) Filed: **Mar. 15, 2005**

(30) **Foreign Application Priority Data**

Sep. 17, 2004 (ZA) F2004/1234

(51) **LOC (8) Cl.** **24-03**

(52) **U.S. Cl.** **D24/155**

(58) **Field of Classification Search** D24/180-181,
D24/176, 155-156, 107; 433/37-43, 76,
433/173, 29, 32; D13/108; 607/143, 37; 362/804,
362/171; D7/584-587, 624.2

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

| | | | | | | |
|-----------|---|---|---------|-----------------|-------|---------|
| 1,641,095 | A | * | 8/1927 | Pernet | | 607/143 |
| 3,293,663 | A | * | 12/1966 | Cronin | | D24/155 |
| 3,528,109 | A | * | 9/1970 | Scales | | D24/155 |
| D249,957 | S | * | 10/1978 | Eicher et al. | | D24/155 |
| D277,607 | S | * | 2/1985 | Himeno | | D24/155 |
| D290,877 | S | * | 7/1987 | Giampapa et al. | | D24/155 |

| | | | | | | |
|-----------|----|---|--------|-----------------|-------|---------|
| D290,879 | S | * | 7/1987 | Giampapa et al. | | D24/155 |
| D296,714 | S | * | 7/1988 | Averill et al. | | D24/155 |
| D471,406 | S | * | 3/2003 | Wellner | | D7/584 |
| 6,740,122 | B1 | * | 5/2004 | Pajotin | | 606/151 |
| D493,224 | S | * | 7/2004 | Cosgrove | | D24/155 |
| D516,025 | S | * | 2/2006 | Quinn | | D13/108 |

* cited by examiner

Primary Examiner—Charles A. Rademaker

(74) *Attorney, Agent, or Firm*—Fitch, Even, Tabin & Flannery

(57) **CLAIM**


The ornamental design for a joint prosthesis component, as shown and described.

DESCRIPTION

FIG. 1 is a left side view of a joint prosthesis component incorporating the design of my invention; FIG. 2 is a three dimensional view from the top left of the joint prosthesis component of FIG. 1; and, FIG. 3 is a three dimensional view from the top of the joint prosthesis component of FIG. 1.

The joint prosthesis component includes a truncated generally hemispherical body which is delimited at an equatorial end by a plane inclined at an angle relative to an equatorial plane and in which a centre point of the hemispherical body lies, and which is delimited at a polar end by a plane which is parallel to the equatorial plane and spaced therefrom. A cut-out is defined in the body to extend between its ends.

1 Claim, 3 Drawing Sheets






FIGURE 1




FIGURE 2




FIGURE 3