



US00D539031S

(12) **United States Design Patent**
Balchunas et al.

(10) **Patent No.:** **US D539,031 S**

(45) **Date of Patent:** **** Mar. 27, 2007**

(54) **CARRIER POUCH**

(75) Inventors: **Dennis Balchunas**, Boulder, CO (US);
Richard N. Case, Boulder, CO (US)

(73) Assignee: **Nite Ize, Inc.**, Boulder, CO (US)

(**) Term: **14 Years**

(21) Appl. No.: **29/253,614**

(22) Filed: **Feb. 10, 2006**

(51) **LOC (8) Cl.** **03-01**

(52) **U.S. Cl.** **D3/226; D3/228**

(58) **Field of Classification Search** D3/226,
D3/228, 215, 225, 230, 201, 232–233, 218,
D3/219; 224/267, 240, 242, 647, 669, 667,
224/668; 383/10, 29, 42, 93, 95, 97–98, 104,
383/109

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

| | | | | | |
|--------------|---|---------|-----------------|-------|---------|
| D286,315 S | * | 10/1986 | Gregory | | D3/225 |
| 5,392,974 A | | 2/1995 | Johnson-Rabbett | | 224/253 |
| D368,581 S | * | 4/1996 | Cincotta | | D3/218 |
| 5,718,104 A | | 2/1998 | Kennedy | | 224/236 |
| 5,833,100 A | | 11/1998 | Kim | | 224/197 |
| D408,129 S | | 4/1999 | Spraulding | | D3/205 |
| D410,773 S | * | 6/1999 | Case | | D3/228 |
| D428,250 S | * | 7/2000 | Reichardt | | D3/228 |
| D435,722 S | | 1/2001 | Pepping | | D3/218 |
| D458,019 S | | 6/2002 | Gur et al. | | D3/218 |
| D472,372 S | | 4/2003 | Hassett | | D3/218 |
| D472,373 S | | 4/2003 | Hillman | | D3/218 |
| 6,568,576 B1 | | 5/2003 | Godshaw et al. | | 224/647 |
| 6,612,432 B2 | | 9/2003 | Motson | | 206/305 |
| D486,304 S | | 2/2004 | Brown | | D3/218 |
| D495,873 S | | 9/2004 | Badillo et al. | | D3/218 |
| D508,607 S | | 8/2005 | Balchunas | | D3/303 |

* cited by examiner

Primary Examiner—Catherine R. Oliver

(74) *Attorney, Agent, or Firm*—Patton Boggs LLP

(57) **CLAIM**

The ornamental design for a carrier pouch, as shown and described.

DESCRIPTION

FIG. 1 is a front elevational view of a carrier pouch showing our new design;

FIG. 2 is a right side elevational view thereof;

FIG. 3 is a rear elevational view thereof;

FIG. 4 is a left side elevational view thereof;

FIG. 5 is a top plan view thereof;

FIG. 6 is a bottom plan view thereof;

FIG. 7 is a left side perspective view thereof in a closed position;

FIG. 8 is a left side perspective view thereof, similar to FIG. 7, but with the pouch in an open position;

FIG. 9 is a front elevational view of a second embodiment thereof

FIG. 10 is a right side elevational view of the embodiment of FIG. 9;

FIG. 11 is a right side elevational view of the embodiment of FIG. 9;

FIG. 12 is a rear elevational view of the embodiment of FIG. 9


FIG. 13 is a bottom plan view of the embodiment of FIG. 9;

FIG. 14 is a top plan view of the embodiment of FIG. 9;

FIG. 15 is a left side perspective view of the embodiment of FIG. 9; and,

FIG. 16 is a left side perspective view of the embodiment of FIG. 9, similar to FIG. 15, but with the pouch in an open position.

1 Claim, 4 Drawing Sheets






Fig. 1




Fig. 3




Fig. 2




Fig. 4




Fig. 6




Fig. 5




Fig. 7




Fig. 8




Fig. 9




Fig. 10




Fig. 11




Fig. 12




Fig. 13




Fig. 14




Fig. 15




Fig. 16