



US00D539037S

(12) **United States Design Patent** (10) **Patent No.:** **US D539,037 S**
Bergh et al. (45) **Date of Patent:** **** Mar. 27, 2007**

(54) **STORAGE DEVICE ADAPTED FOR
INSERTION BETWEEN TWO VEHICLE
SEATS**

(75) Inventors: **James A. Bergh**, Boulder, CO (US);
Eric S. Hassett, Golden, CO (US)

(73) Assignee: **Case Logic, Inc.**, Longmont, CO (US)

(**) Term: **14 Years**

(21) Appl. No.: **29/214,147**

(22) Filed: **Sep. 27, 2004**

(51) **LOC (8) Cl.** **03-01**

(52) **U.S. Cl.** **D3/313; D12/416**

(58) **Field of Classification Search** D12/422,
D12/419, 415, 416; D3/319, 314, 316
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

2,640,595 A	6/1953	Byford
4,383,626 A	5/1983	Weinblatt
4,635,110 A	1/1987	Weinblatt
4,801,060 A	1/1989	Thompson
D312,727 S	12/1990	Kunewalder
D313,695 S	1/1991	Mawhinney et al.
D318,641 S	7/1991	Schwartz
D318,949 S	8/1991	Mawhinney et al.
5,044,321 A	9/1991	Selph
5,044,577 A	9/1991	Spearman
D324,953 S	3/1992	Swanner
D329,836 S	9/1992	Meyers
D338,104 S	8/1993	Lee
D358,483 S	5/1995	Cross et al.
D360,075 S	7/1995	Cross et al.
5,489,055 A *	2/1996	Levy 224/544
D379,452 S	5/1997	Russell et al.
D380,612 S	7/1997	Kelley et al.
D389,115 S	1/1998	Alves et al.
5,720,458 A	2/1998	Carpenter
5,725,189 A	3/1998	Landy
5,746,363 A	5/1998	Teller et al.

5,771,305 A *	6/1998	Davis 381/386
D396,383 S	7/1998	Hanson
5,868,294 A *	2/1999	Webster 224/275
5,887,723 A	3/1999	Myles et al.
5,887,777 A	3/1999	Myles et al.
D413,299 S	8/1999	Hartmann et al.
5,971,148 A	10/1999	Jackson
D425,474 S	5/2000	Bergh
6,092,705 A	7/2000	Meritt
6,097,448 A	8/2000	Perkins
6,109,434 A	8/2000	Howard, Jr.
D430,534 S *	9/2000	Golenz D12/416

(Continued)

OTHER PUBLICATIONS

U.S. Appl. No. 29/203,199, filed Apr. 2004, Hassett.

Primary Examiner—Louis S. Zarfes

Assistant Examiner—Eric L Goodman

(74) *Attorney, Agent, or Firm*—Sheridan Ross P.C.

(57) **CLAIM**

The ornamental design for a storage device adapted for insertion between two vehicle seats, as shown and described.

DESCRIPTION

FIG. 1 is a front perspective view of a storage device adapted for insertion between two vehicle seats, showing my new design;

FIG. 2 is a top plan view of the invention illustrated in FIG. 1.

FIG. 3 is a front elevation view of the invention shown in FIG. 1;


FIG. 4 is a left elevation view of the invention illustrated in FIG. 1;

FIG. 5 is a bottom plan view of the invention illustrated in FIG. 1;

FIG. 6 is a right elevation view of the invention illustrated in FIG. 1; and,

FIG. 7 is a rear elevation view of the invention illustrated in FIG. 1.

1 Claim, 2 Drawing Sheets



U.S. PATENT DOCUMENTS							
D432,075	S	10/2000	Hassett et al.	D468,101	S	1/2003	Hassett
6,145,661	A	11/2000	Jung	D473,510	S	*	4/2003 Denmeade D12/416
6,216,927	B1	4/2001	Meritt	6,685,016	B2		2/2004 Swaim et al.
D441,341	S	5/2001	Hassett et al.	D494,128	S	*	8/2004 Berger D12/416
6,269,948	B1	8/2001	Jackson	D494,534	S	*	8/2004 Hassett D12/416
6,283,299	B1	9/2001	Lee	2003/0029755	A1	*	2/2003 Ho 206/320
D451,882	S	12/2001	Hassett et al.	2003/0102235	A1		6/2003 Swaim et al.
6,361,009	B1	3/2002	Li	2004/0112931	A1	*	6/2004 Swaim et al. 224/585
6,473,315	B2	10/2002	Denmeade	* cited by examiner			

Fig. 1




Fig. 2





Fig. 3




Fig. 4

Fig. 5





Fig. 6




Fig. 7