



US00D541805S

(12) **United States Design Patent**
Swiader

(10) **Patent No.:** **US D541,805 S**

(45) **Date of Patent:** **** May 1, 2007**

(54) **DATA INPUT AND CURSOR CONTROL DEVICE**

(76) Inventor: **Michael C. Swiader**, 2 Jean St., Rye, NY (US) 10580

(**) Term: **14 Years**

(21) Appl. No.: **29/208,449**

(22) Filed: **Jun. 30, 2004**

(51) **LOC (8) Cl.** **14-02**

(52) **U.S. Cl.** **D14/415; D14/416**

(58) **Field of Classification Search** D14/400, D14/402, 405, 408, 412-419, 356, 388, 439, D14/432; D21/324; 273/148 B; 463/37, 38, 463/46, 47; 345/156-163, 167
See application file for complete search history.

5,825,350 A	10/1998	Case, Jr. et al.	
5,898,421 A	4/1999	Quinn	
D413,880 S	* 9/1999	Barnes et al.	D14/416
6,222,526 B1	4/2001	Holmes	
D441,753 S	* 5/2001	Alviar et al.	D14/413
6,281,883 B1	8/2001	Barker	
6,297,807 B1	10/2001	Eisbach et al.	
6,297,808 B1	10/2001	Yang	
D458,261 S	6/2002	Tsai	
D460,073 S	* 7/2002	Whitehorn et al.	D14/416
D462,685 S	* 9/2002	Yamamoto et al.	D14/415
6,577,298 B2	* 6/2003	Krog	345/161
6,624,806 B2	* 9/2003	Hsu	345/161
D491,947 S	* 6/2004	Hsieh	D14/402
6,892,481 B2	* 5/2005	Yamamoto et al.	37/348

* cited by examiner

Primary Examiner—Prabhakar Deshmukh
(74) *Attorney, Agent, or Firm*—Birch, Stewart, Kolasch & Birch, LLP.

(56) **References Cited**

U.S. PATENT DOCUMENTS

D284,593 S	* 7/1986	Happ	D14/416
4,739,128 A	4/1988	Grisham	
4,795,296 A	1/1989	Jau	
4,862,165 A	8/1989	Gart	
4,994,795 A	2/1991	MacKenzie	
5,175,534 A	12/1992	Thatcher	
5,296,871 A	3/1994	Paley	
D350,736 S	9/1994	Takahashi et al.	
5,355,147 A	10/1994	Lear	
D363,710 S	10/1995	Mateus et al.	
5,485,171 A	1/1996	Copper et al.	
D368,901 S	4/1996	Currid	
5,512,892 A	4/1996	Corballis et al.	
D372,231 S	7/1996	Huang	
D381,701 S	* 7/1997	Salinas	D14/416
5,648,798 A	7/1997	Hamling	
5,668,574 A	9/1997	Jarlance-Huang	
5,698,784 A	12/1997	Hotelling et al.	
5,724,106 A	3/1998	Autry et al.	
5,767,841 A	6/1998	Hartman	
5,786,807 A	* 7/1998	Couch et al.	345/161


(57) **CLAIM**

The ornamental design for a data input and cursor control device, as shown and described.

DESCRIPTION

FIG. 1 is a right side elevational view of a data input and cursor control device showing my new design; FIG. 2 is a left side elevational view thereof; FIG. 3 is a front elevational view thereof; FIG. 4 is a rear elevational view thereof; FIG. 5 is a top plan view thereof; FIG. 6 is a bottom view thereof; FIG. 7 is a right side elevational view of a data input and cursor control device showing my new design; FIG. 8 is a left side elevational view thereof; FIG. 9 is a front elevational view thereof; FIG. 10 is a rear elevational view thereof; FIG. 11 is a top plan view thereof; and, FIG. 12 is a bottom view thereof.

1 Claim, 10 Drawing Sheets






FIG. 1



FIG. 2




FIG. 3




FIG.4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 11




FIG. 12