

US00D543018S

(12) **United States Design Patent** (10) **Patent No.:** **US D543,018 S**
Bates et al. (45) **Date of Patent:** **** May 22, 2007**

(54) **FOB**

D522,234 S * 6/2006 Murphy D3/209
D522,743 S * 6/2006 Lui D3/207

(75) Inventors: **Peter Kirwan Bates**, Framingham, MA (US); **David S. Bonalle**, New Rochelle, NY (US); **Gail A. Francolini**, Fairfield, CT (US); **Samantha S. Ing**, New York, NY (US); **Danielle L. Kunian**, New York, NY (US); **Leigh R. Malnati**, Mountain Lakes, NJ (US); **Danielle R. Nulle**, Atlantic Highlands, NJ (US); **Steven A. Rank**, New York, NY (US); **Lisa E. Skilling-Belmond**, New York, NY (US); **Lisa A. Webb**, Darien, CT (US); **Kevin Young**, South Boston, MA (US)

* cited by examiner

Primary Examiner—Ralf Seifert
(74) *Attorney, Agent, or Firm*—McDermott Will & Emery LLP

(73) Assignee: **American Express Travel Related Services Company, Inc.**, New York, NY (US)

(57) **CLAIM**

The ornamental design for a fob, as shown.

(**) Term: **14 Years**

DESCRIPTION

(21) Appl. No.: **29/251,532**

(22) Filed: **Jan. 9, 2006**

FIG. 1 is an isometric perspective view of an embodiment of a new design of the present invention;
FIG. 2 is a top plan view of the new design of the present invention shown in FIG. 1;
FIG. 3 is a bottom plan view of the new design of the present invention shown in FIG. 1;
FIG. 4 is a right side view of the new design of the present invention shown in FIG. 1;
FIG. 5 is a left side view of the new design of the present invention shown in FIG. 1;
FIG. 6 is a top end view of the new design of the present invention shown in FIG. 1;
FIG. 7 is a bottom end view of the new design of the present invention shown in FIG. 1;
FIG. 8 is an isometric perspective view of a second embodiment of the new design of the present invention;
FIG. 9 is a top plan view of the new design of the present invention shown in FIG. 8;
FIG. 10 is a bottom plan view of the new design of the present invention shown in FIG. 8;
FIG. 11 is a right side view of the new design of the present invention shown in FIG. 8;
FIG. 12 is a left side view of the new design of the present invention shown in FIG. 8;
FIG. 13 is a top end view of the new design of the present invention shown in FIG. 8; and,
FIG. 14 is a bottom end view of the new design of the present invention shown in FIG. 8.

Related U.S. Application Data

(63) Continuation of application No. 29/224,791, filed on Mar. 7, 2005.

(51) **LOC (8) Cl.** **03-01**

(52) **U.S. Cl.** **D3/207**

(58) **Field of Classification Search** D3/207–212;
206/37.1, 38.1; 150/147; 70/456 R, 456 B,
70/458–459; 24/3 K, 3.6, 100; D11/44, 48
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

D418,971 S * 1/2000 Scungio D3/207
D431,355 S * 10/2000 Boyd, Jr. D3/209
D449,734 S * 10/2001 Shing D3/209

1 Claim, 6 Drawing Sheets




FIG. 1




FIG. 3




FIG. 2




FIG. 4




FIG. 5




FIG. 6



FIG. 7



FIG. 8




FIG. 10




FIG. 9




FIG. 11




FIG. 12




FIG. 13




FIG. 14

