

US00D546171S

(12) **United States Design Patent** (10) **Patent No.:** **US D546,171 S**
Tabert (45) **Date of Patent:** **** Jul. 10, 2007**

(54) **HOLDER FOR TARGETS** D457,420 S * 5/2002 Kalat D8/370

(75) Inventor: **W. Ray Tabert**, Oxford, IN (US)

* cited by examiner

(73) Assignee: **Pimmler Holdings, Inc.**, Monticello, IN (US)

Primary Examiner—Holly H. Baynham
(74) *Attorney, Agent, or Firm*—Barnes & Thornburg LLP

(**) Term: **14 Years**

(57) **CLAIM**

(21) Appl. No.: **29/222,490**

The ornamental design for a holder for targets, as shown and described.

(22) Filed: **Jan. 31, 2005**

Related U.S. Application Data

DESCRIPTION

(63) Continuation-in-part of application No. 29/214,949, filed on Oct. 12, 2004, now Pat. No. Des. 531,676.

FIG. 1 illustrates a perspective view, from the rear and left side, of a holder for targets showing an embodiment of my new design;

(51) **LOC (8) Cl.** **08-05**

FIG. 2 illustrates a perspective view, from the rear and right side, of a holder for targets showing the embodiment of my new design illustrated in FIG. 1;

(52) **U.S. Cl.** **D8/370**

FIG. 3 illustrates a rear elevational view of a holder for targets showing the embodiment of my new design illustrated in FIGS. 1–2;

(58) **Field of Classification Search** D8/1, D8/370; 47/46–47; 248/85, 87, 156; 273/407
See application file for complete search history.

FIG. 4 illustrates a front elevational view of a holder for targets showing the embodiment of my new design illustrated in FIGS. 1–3;

(56) **References Cited**

U.S. PATENT DOCUMENTS

518,986	A *	5/1894	Cain	248/87
674,161	A *	5/1901	Brown	248/87
796,214	A *	8/1905	Hughes	47/47
854,178	A *	5/1907	Ruff	248/87
1,016,822	A *	2/1912	Golden	47/47
1,073,114	A *	9/1913	Gudgeon	47/47
1,129,838	A *	3/1915	Allen	47/47
1,537,237	A *	5/1925	Kaestner	248/87
2,004,983	A *	6/1935	Goldberg	47/47
2,079,332	A *	5/1937	Overly	47/47
2,173,217	A *	9/1939	Thomsen	47/47
2,285,522	A *	6/1942	Lawrenz	47/47
2,536,341	A *	1/1951	Asher	248/87
2,894,706	A *	7/1959	Cappio	248/87
3,800,365	A *	4/1974	Bruggert	47/47
4,099,299	A *	7/1978	Bruggert et al.	47/44
4,323,251	A *	4/1982	Loveland et al.	273/407
5,088,666	A *	2/1992	Lang	248/87
6,035,576	A *	3/2000	Bozeman	47/47
D442,075	S *	5/2001	Lay et al.	D8/370

FIG. 5 illustrates a right side elevational view of a holder for targets showing the embodiment of my new design illustrated in FIGS. 1–4;

FIG. 6 illustrates a left side view of a holder for targets showing the embodiment of my new design illustrated in FIGS. 1–5;

FIG. 7 illustrates a top plan view of a holder for targets showing the embodiment of my new design illustrated in FIGS. 1–6;

FIG. 8 illustrates a bottom plan view of a holder for targets showing the embodiment of my new design illustrated in FIGS. 1–7;

FIG. 9 illustrates a perspective view, from the front and right side, of a holder for targets showing the embodiment of my new design illustrated in FIGS. 1–8, in “knocked-down” configuration for shipping, storage, display or the like;




FIG. 10 illustrates a top plan view of a holder for targets showing the embodiment of my new design illustrated in FIGS. 1-9, in the configuration illustrated in FIG. 9;

FIG. 11 illustrates a perspective view, from the front and left side, of a holder for targets showing the embodiment of my new design illustrated in FIGS. 1-10, in the configuration illustrated in FIGS. 9-10;

FIG. 12 illustrates a front elevational view of a holder for targets showing the embodiment of my new design illustrated in FIGS. 1-11, in the configuration illustrated in FIGS. 9-11;

FIG. 13 illustrates a left side elevational view of a holder for targets showing the embodiment of my new design illustrated in FIGS. 1-12, in the configuration illustrated in FIGS. 9-12;

FIG. 14 illustrates a right side elevational view of a holder for targets showing the embodiment of my new design illustrated in FIGS. 1-13, in the configuration illustrated in FIGS. 9-13;

FIG. 15 illustrates a bottom plan view of a holder for targets showing the embodiment of my new design illustrated in FIGS. 1-14, in the configuration illustrated in FIGS. 9-14; and,

FIG. 16 illustrates a left side elevational view of a holder for targets showing the embodiment of my new design illustrated in FIGS. 1-15, in a configuration between the configuration illustrated in FIGS. 1-8 and the configuration illustrated in FIGS. 9-15.

1 Claim, 16 Drawing Sheets




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 11




FIG. 12



FIG. 13



FIG. 14




FIG. 15




FIG. 16