

US00D546276S

(12) **United States Design Patent** (10) **Patent No.:** **US D546,276 S**  
**Hagman et al.** (45) **Date of Patent:** **\*\* Jul. 10, 2007**

(54) **PORTION OF A BATTERY**

2003/0108786 A1\* 6/2003 Aaltonen et al. .... 429/61  
2005/0074667 A1\* 4/2005 Yang ..... 429/181

(75) Inventors: **Emma Hagman**, Turku (FI); **Jussi Hovi**, Salo (FI)

**FOREIGN PATENT DOCUMENTS**

(73) Assignee: **Nokia Corporation**, Espoo (FI)

|    |           |         |
|----|-----------|---------|
| FI | 20121     | 12/1998 |
| FI | 20125     | 12/1998 |
| FI | 21733     | 3/2001  |
| FI | 22125     | 8/2001  |
| FI | 23042     | 1/2003  |
| FI | 23753     | 12/2004 |
| WO | DM/063870 | 7/2003  |
| WO | DM/063913 | 8/2003  |
| WO | DM/065348 | 6/2004  |

(\*\*) Term: **14 Years**

(21) Appl. No.: **29/205,246**

(22) Filed: **May 12, 2004**

\* cited by examiner

(30) **Foreign Application Priority Data**

Nov. 12, 2003 (FI) ..... M20030266

*Primary Examiner*—Alan P. Douglas

*Assistant Examiner*—Rosemary K. Tarcza

(51) **LOC (8) Cl.** ..... **13-02**

(74) *Attorney, Agent, or Firm*—Banner & Witcoff, Ltd.

(52) **U.S. Cl.** ..... **D13/103**

(58) **Field of Classification Search** ..... D13/102–106,  
D13/110, 118–119, 184; 429/96–100, 163,  
429/176

(57) **CLAIM**

See application file for complete search history.

The ornamental design for a portion of a battery, as shown and described.

(56) **References Cited**

**DESCRIPTION**

**U.S. PATENT DOCUMENTS**

|                |         |                         |         |
|----------------|---------|-------------------------|---------|
| D303,524 S *   | 9/1989  | Siegner et al. ....     | D14/438 |
| D367,042 S *   | 2/1996  | Morrow et al. ....      | D13/184 |
| D387,727 S *   | 12/1997 | Settsu et al. ....      | D13/103 |
| D406,098 S *   | 2/1999  | Walter et al. ....      | D13/103 |
| D423,449 S *   | 4/2000  | Naskali .....           | D13/103 |
| D439,877 S *   | 4/2001  | Vacheron et al. ....    | D13/103 |
| D444,448 S *   | 7/2001  | Robinson et al. ....    | D13/103 |
| D447,730 S     | 9/2001  | Johansson               |         |
| 6,524,732 B1 * | 2/2003  | Iwaizono et al. ....    | 429/7   |
| D492,267 S *   | 6/2004  | Kawajiri et al. ....    | D13/184 |
| D504,109 S *   | 4/2005  | Hagman et al. ....      | D13/103 |
| D515,026 S *   | 2/2006  | Schlieffers et al. .... | D13/103 |

FIG. 1 is a front view of a portion of a battery showing our new design;

FIG. 2 is a rear view thereof;

FIG. 3 is a top view thereof;


FIG. 4 is a bottom view thereof;

FIG. 5 is a perspective top front view thereof;

FIG. 6 is a perspective bottom front view thereof; and,

FIG. 7 is a front view of the label of FIGS. 1-6 shown in isolation as it appears an unassembled state from the battery.

**1 Claim, 3 Drawing Sheets**






FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7