

US00D546278S

(12) **United States Design Patent** (10) **Patent No.:** **US D546,278 S**
Ueno et al. (45) **Date of Patent:** **** Jul. 10, 2007**

(54) **BATTERY**

(75) Inventors: **Noriyuki Ueno**, Moriguchi (JP);
Toshiya Kuwamura, Moriguchi (JP)

(73) Assignee: **Matsushita Electric Industrial Co., Ltd.**, Osaka (JP)

(**) Term: **14 Years**

(21) Appl. No.: **29/257,805**

(22) Filed: **Apr. 11, 2006**

(30) **Foreign Application Priority Data**

Oct. 11, 2005 (JP) 2005-029619

(51) **LOC (8) Cl.** **13-02**

(52) **U.S. Cl.** **D13/103**

(58) **Field of Classification Search** D13/102–106,
D13/110, 118–119, 184; 429/96–100, 163,
429/176

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

5,369,802 A * 11/1994 Murray 455/351
D353,130 S * 12/1994 Aldrich et al. D13/102
D357,897 S * 5/1995 Daio et al. D13/103
5,652,071 A 7/1997 Lake
D423,450 S 4/2000 Buckle
D425,016 S 5/2000 Buckle
D425,477 S * 5/2000 Buckle D13/103
D425,855 S 5/2000 Buckle
D426,189 S * 6/2000 Buckle D13/103
D426,514 S 6/2000 Buckle
D426,515 S 6/2000 Buckle
D426,516 S 6/2000 Buckle
D426,517 S 6/2000 Buckle
D426,806 S 6/2000 Buckle
D426,807 S * 6/2000 Buckle D13/103
D437,824 S * 2/2001 Sakai et al. D13/110
D439,561 S * 3/2001 Lee et al. D13/103
D446,767 S * 8/2001 Black, Jr. D13/103
6,312,848 B1 11/2001 Kilb et al.

D455,715 S * 4/2002 Sakai et al. D13/118
D515,027 S * 2/2006 Groh et al. D13/103
D528,976 S * 9/2006 Tasei et al. D13/103
D528,977 S * 9/2006 Tasei et al. D13/103
2001/0016282 A1 8/2001 Kilb et al.
2004/0191622 A1 9/2004 Han et al.

FOREIGN PATENT DOCUMENTS

JP 644055/10 5/1988
JP 644055/11 5/1988
JP 644055/12 5/1988
JP 644055/13 5/1988
JP 703917/5 5/1988
JP 703917/6 5/1988
JP 703917/7 5/1988
JP 703917/8 5/1988
JP 703917/9 5/1988
JP 733164 5/1988
JP 733164/1 5/1988

(Continued)

Primary Examiner—Alan P. Douglas

Assistant Examiner—Rosemary K. Tarcza

(74) *Attorney, Agent, or Firm*—Brinks Hofer Gilson & Lione

(57) **CLAIM**

We claim the ornamental design for a battery, as shown and described.

DESCRIPTION

FIG. 1 is a top perspective view of a battery of the present invention;

FIG. 2 is a top view thereof;

FIG. 3 is a first side view thereof;


FIG. 4 is a second side view thereof;

FIG. 5 is a bottom view thereof;

FIG. 6 is a third side view thereof; and,

FIG. 7 is a fourth side view thereof.

1 Claim, 3 Drawing Sheets



FOREIGN PATENT DOCUMENTS					
			JP	703919/3	5/1990
			JP	703919/4	5/1990
JP	733165	5/1988	JP	733165/3	5/1990
JP	733165/1	5/1988	JP	733165/4	5/1990
JP	733166	5/1988	JP	733165/5	2/1993
JP	733180	5/1988	JP	848374/1	4/1993
JP	733164/2	12/1989	JP	848374/2	4/1993
JP	733164/3	12/1989	JP	849303/1	4/1993
JP	733164/4	12/1989	JP	722449/5	11/1993
JP	733165/2	12/1989	JP	644055/3	8/1997
JP	777667	12/1989	JP	703919/5	8/1997
JP	777700	12/1989	JP	D1232377	3/2005
JP	644055/14	5/1990	JP	D1232378	3/2005
JP	644055/15	5/1990	JP	D1232379	3/2005
JP	644055/16	5/1990	JP	D1232620	3/2005
JP	644055/17	5/1990	JP	D1232621	3/2005
JP	644055/19	5/1990	JP	D1247823	8/2005
JP	644055/20	5/1990			
JP	644055/24	5/1990			
JP	644055/25	5/1990			
			* cited by examiner		

FIG.1




FIG.2




FIG.3




FIG.4




FIG.5




FIG.6




FIG.7

