US00D547501S

(12) United States Design Patent

Kolpakov

(10) Patent No.: US D547,501 S
(45) Date of Patent: ** Jul. 24, 2007

(54) **HAND AEROSOL FIRE EXTINGUISHER**

(75) Inventor: **Vladimir Petrovich Kolpakov**, Moscow (RU)

(73) Assignee: **R-Amtech International, Inc.**, Bellevue, WA (US)

(**) Term: **14 Years**

(21) Appl. No.: **29/242,925**

(22) Filed: **Nov. 17, 2005**

(30) **Foreign Application Priority Data**

May 19, 2005 (RU) 2005501366

(51) **LOC (8) Cl.** **29-01**
(52) **U.S. Cl.** **D29/126**
(58) **Field of Classification Search** D29/125, D29/126, 127, 128, 129, 130; D9/531, 536; D23/213, 223, 225; 169/30, 70, 71, 72, 73, 169/74, 75, 76, 77, 78, 79, 80, 81, 82, 83, 169/84, 85, 86, 87, 88, 89; 222/324, 394, 222/402.13, 402.14, 402.15, 465.1, 470; 239/302; D8/2
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

1,530,133 A * 3/1925 Maxwell 222/394

(Continued)

FOREIGN PATENT DOCUMENTS

RU	00042754	8/1996
RU	00050088	3/2002

OTHER PUBLICATIONS

Automatic fire extinguishers, p. 147, Lab Safety Supply 1987 general safety equipment and supplies catalogue.*
UDK, 614.845.2 (Oct. 26, 1988).
COT5M publication (Sep. 30, 2003).

Primary Examiner—T. Chase Nelson
(74) *Attorney, Agent, or Firm*—Rothwell, Figg, Ernst & Manbeck, PC

(57) **CLAIM**

The ornamental design for a hand aerosol fire extinguisher, as shown and described.

DESCRIPTION

FIG. **1** is an upper perspective view of a first embodiment of a hand aerosol fire extinguisher in accordance with the present invention.

FIG. **2** is a lower perspective view of the hand aerosol fire extinguisher first embodiment shown in FIG. **1**.

FIG. **3** is a bottom plan view of the first embodiment shown in FIG. **1**.

FIG. **4** is a side elevational view of the first embodiment shown in FIG. **1**.

FIG. **5** is a top plan view of the first embodiment shown in FIG. **1**.

FIG. **6** is an upper perspective view of a second embodiment of the hand aerosol fire extinguisher shown in FIG. **1**, the only difference being that the outlet openings are arranged on a planar surface in the upper hemisphere of the design, instead of being arranged in the top of the curved surface of the upper hemisphere itself as shown in FIG. **1**, it being understood that all other surfaces are the same as those of the first embodiment.

FIG. **7** is a lower perspective view of the hand aerosol fire extinguisher second embodiment shown in FIG. **6**.

FIG. **8** is a bottom plan view of the second embodiment shown in FIG. **6**.

FIG. **9** is a side elevational view of the second embodiment shown in FIG. **6**; and,

FIG. **10** is a top plan view of the second embodiment shown in FIG. **6**.

1 Claim, 4 Drawing Sheets



U.S. PATENT DOCUMENTS

D112,538	S	*	12/1938	Roessner	D29/128
D117,471	S	*	11/1939	Evans	D29/128
D121,620	S	*	7/1940	Saffell	D29/128
D125,482	S	*	2/1941	Roessner	D29/128
D153,854	S	*	5/1949	Cizek	D29/128
D170,533	S	*	10/1953	Irwin	D29/128
2,668,419	A	*	2/1954	Mapes	169/75
D185,957	S	*	8/1959	Bauman	D29/129
2,915,251	A	*	12/1959	North, Jr.	222/402.15
D190,139	S	*	4/1961	Wilson	D29/126
4,197,915	A	*	4/1980	Martin	169/89
D387,270	S	*	12/1997	Bifulco	D9/600
D387,271	S	*	12/1997	Bifulco	D23/225

* cited by examiner



FIG.1



FIG.2



FIG.3



FIG.4



FIG.5



FIG.6



FIG.7

FIG.8



FIG.9



FIG.10