



US00D548627S

(12) **United States Design Patent** (10) **Patent No.:** **US D548,627 S**
Juhng et al. (45) **Date of Patent:** **** Aug. 14, 2007**

(54) **DUAL USE THERMOMETER**

(75) Inventors: **Leslie Juhng**, Philadelphia, PA (US);
Velissa Van Scoyoc, Pottstown, PA
(US); **Mathieu Turpault**, Berwyn, PA
(US)

(73) Assignee: **Becton, Dickinson and Company**,
Franklin Lakes, NJ (US)

(**) Term: **14 Years**

(21) Appl. No.: **29/268,871**

(22) Filed: **Nov. 15, 2006**

(51) **LOC (8) Cl.** **10-04**

(52) **U.S. Cl.** **D10/57**

(58) **Field of Classification Search** D10/57;
374/1-210; 600/549

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

| | | | | |
|-----------------|--------|----------------|-------|--------|
| D489,275 S * | 5/2004 | Wong | | D10/57 |
| D490,327 S * | 5/2004 | Lussier et al. | | D10/57 |
| D525,886 S | 8/2006 | Russak et al. | | |
| 2004/0170216 A1 | 9/2004 | Russak et al. | | |

* cited by examiner

Primary Examiner—Antoine D. Davis

(74) *Attorney, Agent, or Firm*—Alan W. Fiedler

(57) **CLAIM**

The ornamental design for a dual use thermometer, as shown and described.

DESCRIPTION

FIG. 1 is a perspective view of an exemplary embodiment of a dual use thermometer showing our new design, with the supporting arm of the dual use thermometer in a closed position;

FIG. 2 is a front plan view of the dual use thermometer of FIG. 1;

FIG. 3 is a rear plan view of the dual use thermometer of FIG. 1;

FIG. 4 is a left side view of the dual use thermometer of FIG. 1;

FIG. 5 is a right side view of the dual use thermometer of FIG. 1;

FIG. 6 is a view of the top end of the dual use thermometer of FIG. 1;

FIG. 7 is a view of the bottom end of the dual use thermometer of FIG. 1;

FIG. 8 is a perspective view of the dual use thermometer of FIG. 1, with the supporting arm of the dual use thermometer in an open position;

FIG. 9 is a perspective view of the dual use thermometer of FIG. 1, with the supporting arm of the dual use thermometer in an open position, taken from the rear of the thermometer;

FIG. 10 is a perspective view of another exemplary embodiment of a dual use thermometer, with the supporting arm of the dual use thermometer in a closed position;

FIG. 11 is a front plan view of the dual use thermometer of FIG. 10;

FIG. 12 is a rear plan view of the dual use thermometer of FIG. 10;

FIG. 13 is a left side view of the dual use thermometer of FIG. 10;

FIG. 14 is a right side view of the dual use thermometer of FIG. 10;


FIG. 15 is a view of the top end of the dual use thermometer of FIG. 10;

FIG. 16 is a view of the bottom end of the dual use thermometer of FIG. 10;

FIG. 17 is a perspective view of the dual use thermometer of FIG. 10, with the supporting arm of the dual use thermometer in an open position; and,

FIG. 18 is a perspective view of the dual use thermometer of FIG. 10, with the supporting arm of the dual use thermometer in an open position, taken from the rear of the thermometer.

1 Claim, 14 Drawing Sheets






FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 11




FIG. 12



FIG. 13




FIG. 14




FIG. 15




FIG. 16




FIG. 17




FIG. 18