



US00D552343S

(12) **United States Design Patent**
Brandenburg

(10) **Patent No.:** **US D552,343 S**

(45) **Date of Patent:** **** Oct. 9, 2007**

(54) **SENSOR CASE FOR ATTACHMENT TO A SHOE**

DESCRIPTION

(75) Inventor: **Kyle Brandenburg**, Plantation, FL (US)

(73) Assignee: **Mareware, Inc.**, Hollywood, FL (US)

(**) Term: **14 Years**

(21) Appl. No.: **29/267,930**

(22) Filed: **Oct. 25, 2006**

(51) **LOC (8) Cl.** **03-01**

(52) **U.S. Cl.** **D3/215**

(58) **Field of Classification Search** D3/215,
D3/218, 226, 224, 230; 224/219, 222, 267;
D2/905, 946, 972, 916; 36/11.5, 101
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

D507,103 S *	7/2005	Charles, Jr.	D3/215
D515,805 S *	2/2006	Jones	D3/215
D535,085 S *	1/2007	Berg et al.	D2/946
2006/0027615 A1 *	2/2006	Masi	224/222

* cited by examiner

Primary Examiner—Catherine R. Oliver

(74) *Attorney, Agent, or Firm*—Laurence A. Greenberg;
Werner H. Stemer; Ralph E. Locher

(57) **CLAIM**

The ornamental design for a sensor case for attachment to a shoe, as shown and described.

FIG. 1 is a diagrammatic, top-plan view of a sensor case according to the invention in a closed condition;

FIG. 2 is a side-elevational view of the sensor case in the closed condition;

FIG. 3 is an end-elevational view of the sensor case in the closed condition;

FIG. 4 is a bottom-plan view of the sensor case in the closed condition;

FIG. 5 is a perspective view of the sensor case in the closed condition;

FIG. 6 is a bottom-plan view of the sensor case in an open condition;

FIG. 7 is a side-elevational view of the sensor case in the open condition;

FIG. 8 is a top-plan view of the sensor case in an open condition;

FIG. 9 is an end-elevational view of the sensor case in an open condition;

FIG. 10 is a fragmentary, enlarged, bottom-plan view of the sensor case in the open condition, with a sensor, such as an iPod sensor, partly inserted therein;


FIG. 11 is a fragmentary, perspective view of the sensor case placed in a mostly open condition and inserted beneath laces of a shoe;

FIG. 12 is a view similar to FIG. 11, with the sensor case being closed over the laces; and,

FIG. 13 is another view similar to FIGS. 11 and 12 of the sensor case in a fully closed condition over the laces.

The broken lines represent top-stitching.

1 Claim, 3 Drawing Sheets






Fig 3




Fig 5




Fig 1




Fig 2




Fig 4



Fig 9




Fig 10




Fig 6




Fig 7




Fig 8




Fig 11




Fig 12




Fig 13