



US00D553946S

(12) **United States Design Patent** (10) **Patent No.:** **US D553,946 S**  
**Story, Jr.** (45) **Date of Patent:** **\*\* Oct. 30, 2007**

(54) **LOCK**

(76) Inventor: **Paul J. Story, Jr.**, 812 E. Worthington Ave., Charlotte, NC (US) 28203

(\*\*) Term: **14 Years**

(21) Appl. No.: **29/236,136**

(22) Filed: **Aug. 11, 2005**

(51) **LOC (8) Cl.** ..... **08-07**

(52) **U.S. Cl.** ..... **D8/331**

(58) **Field of Classification Search** ..... D8/330-348  
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

D298,911 S \* 12/1988 Burke, Sr. .... D8/330

D350,914 S \* 9/1994 Gershenson ..... D8/342

\* cited by examiner

*Primary Examiner*—Mitchell Siegel

(74) *Attorney, Agent, or Firm*—Ralph H. Dougherty

(57) **CLAIM**

The ornamental design for a lock, as shown and described.

#### DESCRIPTION

FIG. 1 is a perspective view of the invented lock, showing the new design;

FIG. 2 is a top view thereof;

FIG. 3 is a left side elevational view thereof;

FIG. 4 is a front elevational view thereof, the rear view being a mirror image;

FIG. 5 is a right side elevational view thereof;

FIG. 6 is a bottom view thereof; and

FIG. 7 is a perspective view of the invented lock for a machined member showing its location in use within another member.

FIG. 8 is a perspective view of an alternative embodiment of the invented lock showing the alternative design.

FIG. 9 is a side view of the embodiment of FIG. 8 in use locking a machined member within another member.

FIG. 10 is a top view of the embodiment of FIG. 8;

FIG. 11 is a left side elevational view thereof;

FIG. 12 is a front elevational view thereof, the rear view being a mirror image;

FIG. 13 is a right side elevational view thereof; and

FIG. 14 is a bottom view thereof.

FIG. 15 is a top view of a second alternative embodiment of the invented lock showing the alternative design;

FIG. 16 is a left side elevational view thereof;

FIG. 17 is a front elevational view thereof, the rear view being a mirror image;

FIG. 18 is a right side elevational view thereof; and

FIG. 19 is a bottom view thereof.

FIG. 20 is a top view of a third alternative embodiment of the invented lock showing the alternative design;

FIG. 21 is a left side elevational view thereof;


FIG. 22 is a front elevational view thereof, the rear view being a mirror image;

FIG. 23 is a right side elevational view thereof; and,


FIG. 24 is a bottom view thereof.

Material shown in dotted lines shows the environment in which the invented design is used, and forms no part of the invented design.


**1 Claim, 8 Drawing Sheets**




***Fig. 1***




*Fig.2*




*Fig.3*




*Fig.4*




*Fig.5*




*Fig.6*




*Fig. 7*




***Fig. 8***




***Fig.9***




***Fig.10***




***Fig.11***




***Fig.12***




***Fig.13***




***Fig.14***




*Fig.15*




*Fig.16*




*Fig.17*



*Fig.18*




*Fig.19*







*Fig.20*




*Fig.21*



*Fig.22*



*Fig.23*



*Fig.24*

