



US00D553946S

(12) **United States Design Patent** (10) **Patent No.:** **US D553,946 S**
Story, Jr. (45) **Date of Patent:** **** Oct. 30, 2007**

(54) **LOCK**

(76) Inventor: **Paul J. Story, Jr.**, 812 E. Worthington Ave., Charlotte, NC (US) 28203

(**) Term: **14 Years**

(21) Appl. No.: **29/236,136**

(22) Filed: **Aug. 11, 2005**

(51) **LOC (8) Cl.** **08-07**

(52) **U.S. Cl.** **D8/331**

(58) **Field of Classification Search** D8/330-348
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

D298,911 S * 12/1988 Burke, Sr. D8/330

D350,914 S * 9/1994 Gershenson D8/342

* cited by examiner

Primary Examiner—Mitchell Siegel

(74) *Attorney, Agent, or Firm*—Ralph H. Dougherty

(57) **CLAIM**

The ornamental design for a lock, as shown and described.

DESCRIPTION

FIG. 1 is a perspective view of the invented lock, showing the new design;

FIG. 2 is a top view thereof;

FIG. 3 is a left side elevational view thereof;

FIG. 4 is a front elevational view thereof, the rear view being a mirror image;

FIG. 5 is a right side elevational view thereof;

FIG. 6 is a bottom view thereof; and

FIG. 7 is a perspective view of the invented lock for a machined member showing its location in use within another member.

FIG. 8 is a perspective view of an alternative embodiment of the invented lock showing the alternative design.

FIG. 9 is a side view of the embodiment of FIG. 8 in use locking a machined member within another member.

FIG. 10 is a top view of the embodiment of FIG. 8;

FIG. 11 is a left side elevational view thereof;

FIG. 12 is a front elevational view thereof, the rear view being a mirror image;

FIG. 13 is a right side elevational view thereof; and

FIG. 14 is a bottom view thereof.

FIG. 15 is a top view of a second alternative embodiment of the invented lock showing the alternative design;

FIG. 16 is a left side elevational view thereof;

FIG. 17 is a front elevational view thereof, the rear view being a mirror image;

FIG. 18 is a right side elevational view thereof; and

FIG. 19 is a bottom view thereof.

FIG. 20 is a top view of a third alternative embodiment of the invented lock showing the alternative design;

FIG. 21 is a left side elevational view thereof;

FIG. 22 is a front elevational view thereof, the rear view being a mirror image;

FIG. 23 is a right side elevational view thereof; and,

FIG. 24 is a bottom view thereof.

Material shown in dotted lines shows the environment in which the invented design is used, and forms no part of the invented design.

1 Claim, 8 Drawing Sheets




Fig. 1




Fig.2




Fig.3




Fig.4




Fig.5




Fig.6




Fig. 7




Fig. 8




Fig. 9




Fig.10




Fig.11




Fig.12




Fig.13




Fig.14




Fig.15




Fig.16




Fig.17




Fig.18




Fig.19




Fig. 20




Fig. 21




Fig. 22




Fig. 23




Fig. 24

