



US00D558135S

(12) **United States Design Patent**  
**Miyasaka**

(10) **Patent No.:** **US D558,135 S**

(45) **Date of Patent:** **\*\* Dec. 25, 2007**

(54) **TREAD PORTION OF AN AUTOMOBILE TIRE**

(75) Inventor: **Atsushi Miyasaka**, Chuo-ku (JP)

(73) Assignee: **Bridgestone Corporation**, Tokyo (JP)

(\*\*) Term: **14 Years**

(21) Appl. No.: **29/260,767**

(22) Filed: **Jun. 1, 2006**

(30) **Foreign Application Priority Data**

Dec. 1, 2005 (JP) ..... 2005-035551

(51) **LOC (8) Cl.** ..... **12-15**

(52) **U.S. Cl.** ..... **D12/587; D12/588**

(58) **Field of Classification Search** ..... D12/587,  
D12/588, 583.585, 589, 590, 591; 152/209.1,  
152/209.18, 209.25, 209.26, 209.27  
See application file for complete search history.

(56) **References Cited**

**U.S. PATENT DOCUMENTS**

D531,114 S \* 10/2006 Dixon et al. .... D12/587

**OTHER PUBLICATIONS**

Nexen DH II-60/65 Tire, 2004 Tread Design Guide, Jan. 2004, p. 56. 2/1.\*

“Tyre Catalogue 2005” Japan Patent Office Design Division Document Card No. HC17037227, dated Sep. 26, 2005.

\* cited by examiner

*Primary Examiner*—Robert M. Spear

*Assistant Examiner*—Katrina A Kile

(74) *Attorney, Agent, or Firm*—Sughrue Mion, PLLC

(57) **CLAIM**

The ornamental design for a tread portion of an automobile tire, as shown and described.

**DESCRIPTION**

FIG. 1 is a perspective view of an automobile tire, it being understood that the tread pattern repeats uniformly throughout the circumference of the tire.

FIG. 2 is a front elevation view thereof. A top plan view, a bottom plan view, and a rear elevation view are identical with the front elevation view.

FIG. 3 is a left side elevation view thereof. A right side elevation view is identical with the left side elevation view.

FIG. 4 is an enlarged fragmentary front view thereof; and, FIG. 5 is an enlarged cross-sectional view thereof taken along line 5—5 in FIG. 4.

The portion of the article shown in broken lines is for illustrative purpose only and forms no part of the claimed design.

In the drawings, the dark stippled surface shading represents the recessed portion of the tread grooves, having the depth shown in FIG. 5.

**1 Claim, 5 Drawing Sheets**





FIG. 1



# FIG. 2




FIG. 3




FIG. 4




FIG. 5

