



US00D559467S

(12) **United States Design Patent**
Petzl

(10) **Patent No.:** **US D559,467 S**
(45) **Date of Patent:** **** Jan. 8, 2008**

(54) **HARNESS**

(75) Inventor: **Paul Petzl**, Barraux (FR)

(73) Assignee: **Zedel**, Crolles (FR)

(**) Term: **14 Years**

(21) Appl. No.: **29/274,943**

(22) Filed: **Jun. 12, 2007**

Related U.S. Application Data

(62) Division of application No. 29/269,643, filed on Dec. 6, 2006.

(30) **Foreign Application Priority Data**

Jun. 6, 2006 (EM) 000 543236

(51) **LOC (8) Cl.** **29-02**

(52) **U.S. Cl.** **D29/101.1**

(58) **Field of Classification Search** D29/100,
D29/100.1, 100.2, 101.4, 122, 124; D21/683;
D30/152; 2/311; 119/770, 857; 182/3-6,
182/9, 133; 244/151 R; 297/485
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

2,252,998 A	8/1941	Wachtel	
2,344,031 A	3/1944	De Shano	
2,979,028 A	4/1961	Zakely	
3,159,241 A	12/1964	Martin	
3,424,134 A *	1/1969	Rosenblum	182/3
3,757,893 A	9/1973	Hobbs	
4,197,816 A	4/1980	Lusch	
5,145,027 A	9/1992	Petzl et al.	
5,445,114 A	8/1995	Walker	
5,615,750 A	4/1997	Phillips	

(Continued)

FOREIGN PATENT DOCUMENTS

EP 1516646 A1 3/2005

Primary Examiner—T. Chase Nelson

Assistant Examiner—Karen Acker

(74) *Attorney, Agent, or Firm*—Oliff & Berridge, PLC

(57) **CLAIM**

The ornamental design for a harness, as shown and described.

DESCRIPTION

FIG. 1 is a perspective view of the harness according to a first embodiment;

FIG. 2 is a front view thereof according to the first embodiment;

FIG. 3 is a right-side view thereof according to the first embodiment;

FIG. 4 is a left-side view thereof according to the first embodiment;

FIG. 5 is a rear view thereof according to the first embodiment;

FIG. 6 is a front view of a belt of the harness according to the first embodiment, the belt being shown in an unattached and separated position;

FIG. 7 is a perspective view of the harness according to a second embodiment;

FIG. 8 is a front view thereof according to the second embodiment;


FIG. 9 is a right-side view thereof according to the second embodiment;

FIG. 10 is a left-side view thereof according to the second embodiment;

FIG. 11 is a rear view thereof according to the second embodiment; and,

FIG. 12 is a front view of a belt of the harness according to the second embodiment, the belt being shown in an unattached and separated position.

1 Claim, 12 Drawing Sheets



US D559,467 S

Page 2

U.S. PATENT DOCUMENTS

D389,890 S *	1/1998	Diodato	D21/805	6,283,248 B1	9/2001	Groover	
5,896,859 A *	4/1999	Carroll	128/845	D454,986 S *	3/2002	Casebolt et al.	D29/101.1
D411,336 S *	6/1999	Kline	D29/100	6,374,946 B1	4/2002	Petzl et al.	
D417,753 S *	12/1999	Wiley	D29/101.1	6,431,313 B1	8/2002	Petzl et al.	
6,050,364 A	4/2000	Popall et al.		D474,874 S *	5/2003	Taylor	D2/743
D429,386 S	8/2000	Tingler		2002/0042942 A1	4/2002	Colorado	
6,244,379 B1	6/2001	Larson					

* cited by examiner




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 11




FIG. 12