



US00D560565S

(12) **United States Design Patent**
Kalous

(10) **Patent No.:** **US D560,565 S**

(45) **Date of Patent:** **** Jan. 29, 2008**

(54) **PIN CAP**

7,128,331 B2 * 10/2006 Brackett et al. 280/491.2
D546,663 S * 7/2007 Recknagel et al. D8/339

(75) Inventor: **Scott Kalous**, Libertyville, IL (US)

* cited by examiner

(73) Assignee: **Master Lock Company LLC**, Oak Creek, WI (US)

Primary Examiner—Doris Clark

Assistant Examiner—Michael A. Pratt

(**) Term: **14 Years**

(74) *Attorney, Agent, or Firm*—Calfee, Halter & Griswold LLP

(21) Appl. No.: **29/232,230**

(57) **CLAIM**

(22) Filed: **Jun. 16, 2005**

I claim the ornamental design for a pin cap, as shown and described.

(51) **LOC (8) Cl.** **12-16**

(52) **U.S. Cl.** **D12/159**

(58) **Field of Classification Search** D12/106,
D12/115, 116, 161, 162, 199; 280/402, 403,
280/404, 405.1, 405.2, 407, 407.1, 416.2,
280/455.1, 491.5, 186, 433, 434, 438 R;
D21/701; D8/1, 28, 16, 330, 367, 344
See application file for complete search history.

DESCRIPTION

FIG. 1 is a perspective view of a pin cap showing my new design; shown fixed to a receiver pin assembly,

FIG. 2 is a perspective view thereof;

FIG. 3 is a top plan view thereof;

FIG. 4 is a side elevation view thereof;

FIG. 5 is a front elevation view thereof; and,

FIG. 6 is a bottom plan view thereof.


The broken line showing of a receiver pin assembly is for environmental purposes only and forms no part of the claimed design. The broken line showing of the upper and lower portions of a pin cap defines the boundary of the claimed design.

(56) **References Cited**

U.S. PATENT DOCUMENTS

3,247,753	A *	4/1966	Appleberry	280/515
3,865,407	A	2/1975	Klassen		
4,193,611	A *	3/1980	Fisk	280/416.1
4,671,528	A *	6/1987	Thompson	280/504
D356,763	S	3/1995	Herrick		
6,145,866	A *	11/2000	Peter	280/515
6,415,475	B1 *	7/2002	Dixon	280/514

1 Claim, 1 Drawing Sheet






FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6

UNITED STATES PATENT AND TRADEMARK OFFICE
CERTIFICATE OF CORRECTION

PATENT NO. : Des. 560,565 S
APPLICATION NO. : 29/232230
DATED : January 29, 2008
INVENTOR(S) : Scott Kalous

Page 1 of 4

It is certified that error appears in the above-identified patent and that said Letters Patent is hereby corrected as shown below:

TITLE PAGE

In the Figure Description:

Please replace the current description with the following:

Figure 1 is a perspective view of an embodiment of the present invention, showing a pin cap fixed to a receiver pin assembly shown in phantom;

Figure 2 is a perspective view of the pin cap of Figure 1;

Figure 3 is a top view of the pin cap of Figure 1;

Figure 4 is a side view of the pin cap of Figure 1;

Figure 5 is a front view of the pin cap of Figure 1;

Figure 6 is a bottom view of the pin cap of Figure 1;

Figure 7 is a rear view of the pin cap of Figure 1, as shown from the opposite view of Figure 5;

Figure 8 is a side view of the pin cap of Figure 1, as shown from the opposite view of Figure 4;

Figure 9 is a perspective view of another embodiment of the present invention, showing a pin cap fixed to a receiver pin assembly shown in phantom;

Figure 10 is a perspective view of the pin cap of Figure 9;

Figure 11 is a top view of the pin cap of Figure 9;

Figure 12 is a side view of the pin cap of Figure 9;

Figure 13 is a front view of the pin cap of Figure 9;

Figure 14 is a bottom view of the pin cap of Figure 9;

UNITED STATES PATENT AND TRADEMARK OFFICE
CERTIFICATE OF CORRECTION

PATENT NO. : Des. 560,565 S
APPLICATION NO. : 29/232230
DATED : January 29, 2008
INVENTOR(S) : Scott Kalous

Page 2 of 4

It is certified that error appears in the above-identified patent and that said Letters Patent is hereby corrected as shown below:


Figure 15 is a rear view of the pin cap of Figure 9, as shown from the opposite view of Figure 13;

Figure 16 is a side view of the pin cap of Figure 9, as shown from the opposite view of Figure 12.

Please replace incorrect Figs. 1-6 with correct Figures 1-16.

Signed and Sealed this

Sixth Day of May, 2008

A handwritten signature in black ink that reads "Jon W. Dudas". The signature is written in a cursive style with a large, looped initial "J".

JON W. DUDAS
Director of the United States Patent and Trademark Office




FIG. 1




FIG. 2




FIG. 3




FIG. 7




FIG. 4




FIG. 5




FIG. 8




FIG. 6




FIG. 9




FIG. 10




FIG. 11




FIG. 15




FIG. 12




FIG. 13




FIG. 16




FIG. 14

UNITED STATES PATENT AND TRADEMARK OFFICE
CERTIFICATE OF CORRECTION

PATENT NO. : Des. 560,565 S
APPLICATION NO. : 29/232230
DATED : January 29, 2008
INVENTOR(S) : Scott Kalous

Page 1 of 5

It is certified that error appears in the above-identified patent and that said Letters Patent is hereby corrected as shown below:

TITLE PAGE

Delete the title page and substitute therefor the attached title page.

In the Figure Description:

Please replace the current description with the following:

Figure 1 is a perspective view of an embodiment of the present invention, showing a pin cap fixed to a receiver pin assembly shown in phantom;

Figure 2 is a perspective view of the pin cap of Figure 1;

Figure 3 is a top view of the pin cap of Figure 1;

Figure 4 is a side view of the pin cap of Figure 1;

Figure 5 is a front view of the pin cap of Figure 1;

Figure 6 is a bottom view of the pin cap of Figure 1;

Figure 7 is a rear view of the pin cap of Figure 1, as shown from the opposite view of Figure 5;

Figure 8 is a side view of the pin cap of Figure 1, as shown from the opposite view of Figure 4;

Figure 9 is a perspective view of another embodiment of the present invention, showing a pin cap fixed to a receiver pin assembly shown in phantom;

Figure 10 is a perspective view of the pin cap of Figure 9;

Figure 11 is a top view of the pin cap of Figure 9;

Figure 12 is a side view of the pin cap of Figure 9;

Figure 13 is a front view of the pin cap of Figure 9;

Figure 14 is a bottom view of the pin cap of Figure 9;

UNITED STATES PATENT AND TRADEMARK OFFICE
CERTIFICATE OF CORRECTION

PATENT NO. : Des. 560,565 S
APPLICATION NO. : 29/232230
DATED : January 29, 2008
INVENTOR(S) : Scott Kalous

Page 2 of 5

It is certified that error appears in the above-identified patent and that said Letters Patent is hereby corrected as shown below:

Figure 15 is a rear view of the pin cap of Figure 9, as shown from the opposite view of Figure 13;

Figure 16 is a side view of the pin cap of Figure 9, as shown from the opposite view of Figure 12.

Please replace incorrect Figs. 1-6 with correct Figures 1-16.

This certificate supersedes the Certificate of Correction issued May 6, 2008.

Signed and Sealed this

Tenth Day of June, 2008

A handwritten signature in black ink that reads "Jon W. Dudas". The signature is written in a cursive style with a large, looped initial "J".

JON W. DUDAS
Director of the United States Patent and Trademark Office

(12) **United States Design Patent**
Kalous

(10) **Patent No.:** **US D560,565 S**
(45) **Date of Patent:** **** Jan. 29, 2008**

(54) **PIN CAP**

7,128,331 B2 * 10/2006 Brackett et al. 280/491.2
D546,663 S * 7/2007 Recknagel et al. D8/339

(75) **Inventor:** **Scott Kalous**, Libertyville, IL (US)

* cited by examiner

(73) **Assignee:** **Master Lock Company LLC**, Oak Creek, WI (US)

Primary Examiner—Doris Clark
Assistant Examiner—Michael A. Pratt
(74) *Attorney, Agent, or Firm*—Caffee, Halter & Griswold LLP

(**) **Term:** **14 Years**

(21) **Appl. No.:** **29/232,230**

(57) **CLAIM**

(22) **Filed:** **Jun. 16, 2005**

I claim the ornamental design for a pin cap, as shown and described.

(51) **LOC (8) Cl.** **12-16**

(52) **U.S. Cl.** **D12/159**

(58) **Field of Classification Search** **D12/106,**
D12/115, 116, 161, 162, 199; 280/402, 403,
280/404, 405.1, 405.2, 407, 407.1, 416.2,
280/455.1, 491.5, 186, 433, 434, 438 R;
D21/701; D8/1, 28, 16, 330, 367, 344

DESCRIPTION

See application file for complete search history.

FIG. 1 is a perspective view of a pin cap showing my new design; shown fixed to a receiver pin assembly,
FIG. 2 is a perspective view thereof;
FIG. 3 is a top plan view thereof;
FIG. 4 is a side elevation view thereof;
FIG. 5 is a front elevation view thereof; and,
FIG. 6 is a bottom plan view thereof.


(56) **References Cited**

U.S. PATENT DOCUMENTS

3,247,753 A * 4/1966 Appleberry 280/515
3,865,487 A 2/1975 Klassen
4,193,611 A * 3/1980 Fisk 280/416.1
4,671,528 A * 6/1987 Thompson 280/504
D356,763 S 3/1995 Herrick
6,145,866 A * 11/2000 Peter 280/515
6,415,475 B1 * 7/2002 Dixon 280/514

The broken line showing of a receiver pin assembly is for environmental purposes only and forms no part of the claimed design. The broken line showing of the upper and lower portions of a pin cap defines the boundary of the claimed design.

1 Claim, 1 Drawing Sheet






FIG. 1




FIG. 2




FIG. 3




FIG. 7




FIG. 4




FIG. 5




FIG. 8




FIG. 6




FIG. 9




FIG. 10




FIG. 11




FIG. 15




FIG. 12




FIG. 13




FIG. 16




FIG. 14