



US00D562763S

(12) **United States Design Patent** (10) **Patent No.:** **US D562,763 S**
Kingston et al. (45) **Date of Patent:** **** Feb. 26, 2008**

(54) **LIGHTING DEVICE CHARGER**

(75) Inventors: **Ronald J. Kingston**, Syracuse, NY (US); **Donwoong Kang**, Camillus, NY (US); **Scott W. Osiecki**, Skaneateles, NY (US)

(73) Assignee: **Eveready Battery Company, Inc.**, St. Louis, MO (US)

(**) Term: **14 Years**

(21) Appl. No.: **29/286,609**

(22) Filed: **May 14, 2007**

(51) **LOC (8) Cl.** **13-02**

(52) **U.S. Cl.** **D13/108; D13/137.2**

(58) **Field of Classification Search** D13/107-110, D13/118-119, 137.1, 137.2, 184; D14/251, D14/253, 432, 434; D26/26; 320/107-115
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

- D211,387 S 6/1968 Muller
- D253,853 S 1/1980 Gerber
- 4,636,703 A * 1/1987 Tohya et al. 320/110
- D311,067 S 10/1990 Chabria
- D317,310 S 6/1991 Schwartz
- D328,357 S 7/1992 Schneider
- D334,170 S * 3/1993 Rams et al. D13/108
- D343,469 S 1/1994 Yuen
- D343,470 S 1/1994 Yuen
- D356,174 S 3/1995 Lo
- D370,070 S 5/1996 Kay
- D411,324 S 6/1999 Roorda
- D411,635 S 6/1999 Philipot et al.
- D411,823 S * 7/1999 Jacobs et al. D13/107
- D432,689 S * 10/2000 Yuen D26/38
- D434,863 S 12/2000 Boessel
- D437,429 S * 2/2001 Boessel D26/26
- 6,227,677 B1 5/2001 Willis
- D443,500 S * 6/2001 Luu D8/353
- D444,449 S * 7/2001 Yamamoto D13/107

- D449,402 S 10/2001 Echito
- D450,868 S 11/2001 Maximilian-Yee
- D459,521 S 6/2002 Echito
- D464,865 S * 10/2002 Luu D8/353
- D469,339 S * 1/2003 Luu D8/353
- D477,432 S 7/2003 Parsons
- D491,305 S 6/2004 Copeland
- D496,485 S 9/2004 Stekelenburg

(Continued)

FOREIGN PATENT DOCUMENTS

WO 2007/090112 A2 8/2007

Primary Examiner—Cathron Brooks
Assistant Examiner—Rosemary K Tarcza
(74) *Attorney, Agent, or Firm*—Gregory J. Adams

(57) **CLAIM**

We claim the ornamental design for a lighting device charger, as shown and described.

DESCRIPTION

FIG. 1 is a right top perspective view of the lighting device charger of the present invention.

FIG. 2 is a front view of the lighting device charger of the present invention.

FIG. 3 is a back side view of the lighting device charger of the present invention.


FIG. 4 is a right side view of the lighting device charger of the present invention.

FIG. 5 is a top view of the lighting device charger of the present invention.

FIG. 6 is a bottom view of the lighting device charger of the present invention.

The broken line showing is included for the purpose of illustrating environmental features and forms no part of the claimed design.

1 Claim, 5 Drawing Sheets



US D562,763 S

Page 2

U.S. PATENT DOCUMENTS

7,048,414 B2	5/2006	Weber		7,150,540 B2	12/2006	Kovacik et al.	
D523,394 S *	6/2006	Lie	D13/107	D539,216 S	3/2007	Hamaguchi	
D523,982 S	6/2006	Doong		D539,456 S	3/2007	Sassoon et al.	
D526,271 S *	8/2006	Lie	D13/107	D550,615 S *	9/2007	Tong	D13/107
D527,129 S	8/2006	Hodgson		D551,163 S *	9/2007	Hamasaki	D13/107
D527,132 S	8/2006	Citterio		2004/0145890 A1	7/2004	Liao	
D532,920 S	11/2006	Echito		2005/0231941 A1	10/2005	Huang	

* cited by examiner




Fig. 1




Fig. 2




Fig. 3




Fig. 4




Fig. 5




Fig. 6