



US00D562763S

(12) **United States Design Patent** (10) **Patent No.:** **US D562,763 S**
Kingston et al. (45) **Date of Patent:** **** Feb. 26, 2008**

(54) **LIGHTING DEVICE CHARGER**

(75) Inventors: **Ronald J. Kingston**, Syracuse, NY
(US); **Donwoong Kang**, Camillus, NY
(US); **Scott W. Osiecki**, Skaneateles,
NY (US)

(73) Assignee: **Eveready Battery Company, Inc.**, St.
Louis, MO (US)

(**) Term: **14 Years**

(21) Appl. No.: **29/286,609**

(22) Filed: **May 14, 2007**

(51) **LOC (8) Cl.** **13-02**

(52) **U.S. Cl.** **D13/108; D13/137.2**

(58) **Field of Classification Search** D13/107-110,
D13/118-119, 137.1, 137.2, 184; D14/251,
D14/253, 432, 434; D26/26; 320/107-115
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

D211,387 S	6/1968	Muller	
D253,853 S	1/1980	Gerber	
4,636,703 A *	1/1987	Tohya et al.	320/110
D311,067 S	10/1990	Chabria	
D317,310 S	6/1991	Schwartz	
D328,357 S	7/1992	Schneider	
D334,170 S *	3/1993	Rams et al.	D13/108
D343,469 S	1/1994	Yuen	
D343,470 S	1/1994	Yuen	
D356,174 S	3/1995	Lo	
D370,070 S	5/1996	Kay	
D411,324 S	6/1999	Roorda	
D411,635 S	6/1999	Philipot et al.	
D411,823 S *	7/1999	Jacobs et al.	D13/107
D432,689 S *	10/2000	Yuen	D26/38
D434,863 S	12/2000	Boessel	
D437,429 S *	2/2001	Boessel	D26/26
6,227,677 B1	5/2001	Willis	
D443,500 S *	6/2001	Luu	D8/353
D444,449 S *	7/2001	Yamamoto	D13/107

D449,402 S	10/2001	Echito	
D450,868 S	11/2001	Maximilian-Yee	
D459,521 S	6/2002	Echito	
D464,865 S *	10/2002	Luu	D8/353
D469,339 S *	1/2003	Luu	D8/353
D477,432 S	7/2003	Parsons	
D491,305 S	6/2004	Copeland	
D496,485 S	9/2004	Stekelenburg	

(Continued)

FOREIGN PATENT DOCUMENTS

WO 2007/090112 A2 8/2007

Primary Examiner—Cathron Brooks
Assistant Examiner—Rosemary K Tarcza
(74) *Attorney, Agent, or Firm*—Gregory J. Adams

(57) **CLAIM**

We claim the ornamental design for a lighting device charger, as shown and described.

DESCRIPTION

FIG. 1 is a right top perspective view of the lighting device charger of the present invention.

FIG. 2 is a front view of the lighting device charger of the present invention.

FIG. 3 is a back side view of the lighting device charger of the present invention.


FIG. 4 is a right side view of the lighting device charger of the present invention.

FIG. 5 is a top view of the lighting device charger of the present invention.

FIG. 6 is a bottom view of the lighting device charger of the present invention.

The broken line showing is included for the purpose of illustrating environmental features and forms no part of the claimed design.

1 Claim, 5 Drawing Sheets



US D562,763 S

Page 2

U.S. PATENT DOCUMENTS

7,048,414 B2	5/2006	Weber		7,150,540 B2	12/2006	Kovacik et al.	
D523,394 S *	6/2006	Lie	D13/107	D539,216 S	3/2007	Hamaguchi	
D523,982 S	6/2006	Doong		D539,456 S	3/2007	Sassoon et al.	
D526,271 S *	8/2006	Lie	D13/107	D550,615 S *	9/2007	Tong	D13/107
D527,129 S	8/2006	Hodgson		D551,163 S *	9/2007	Hamasaki	D13/107
D527,132 S	8/2006	Citterio		2004/0145890 A1	7/2004	Liao	
D532,920 S	11/2006	Echito		2005/0231941 A1	10/2005	Huang	

* cited by examiner




Fig. 1




Fig. 2




Fig. 3




Fig. 4




Fig. 5




Fig. 6