



US00D566878S

(12) **United States Design Patent**
Duffy et al.

(10) **Patent No.: US D566,878 S**
(45) **Date of Patent: ** Apr. 15, 2008**

(54) **WALL-MOUNTED LIGHTING FIXTURE**

DESCRIPTION

(75) Inventors: **Roger Duffy**, New York, NY (US);
Peter Magill, New York, NY (US);
Walter Patrick Smith, Basking Ridge,
NJ (US); **Ursula Schneider**, Madrid
(ES); **Mikako Oshima**, New York, NY
(US)

(73) Assignee: **Ivalo Lighting Inc.**, Coopersburg, PA
(US)

(**) Term: **14 Years**

(21) Appl. No.: **29/279,436**

(22) Filed: **May 1, 2007**

(51) **LOC (8) Cl.** **26-03**

(52) **U.S. Cl.** **D26/85**

(58) **Field of Classification Search** D26/72,
D26/85, 88, 89, 121, 122; 362/147, 348-350,
362/367, 432, 806

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

D81,847 S * 8/1930 Roettges D26/122
(Continued)

OTHER PUBLICATIONS

Lighting configuration labeled as No. 2 on p. 304 of the 2005 IKEA
Catalog.*
TYFT wall lamps (6) on p. 305 of the 2005 IKEA Catalog.*

* cited by examiner

Primary Examiner—Clare E Heflin

(74) *Attorney, Agent, or Firm*—Ostrolenk, Faber, Gerb &
Soffen, LLP

(57) **CLAIM**

The ornamental design for a wall-mounted lighting fixture,
as shown and described.

FIG. 1 is a right-front perspective of a first embodiment of
a wall-mounted lighting fixture according to the invention as
seen from above;

FIG. 2 is a front elevation view of the first embodiment;

FIG. 3 is a left side elevation view of the first embodiment
(with the front of the fixture at the right side of the figure);

FIG. 4 is a right side elevation view of the first embodiment
(with the front of the fixture at the left side of the figure);

FIG. 5 is a rear elevation view of the first embodiment;

FIG. 6 is a top plan view of the first embodiment (with the
front of the fixture at the bottom of the figure);

FIG. 7 is a bottom plan view of the first embodiment (with
the front of the fixture at the top of the figure);

FIG. 8 is a right-front perspective of a second embodiment
of a wall-mounted lighting fixture according to the invention
as seen from above which is a mirror image of the first
embodiment about a vertical centerline, and mounted upside
down relative to the first embodiment;

FIG. 9 is a front elevation view of the second embodiment;

FIG. 10 is a left side elevation view of the second embodi-
ment (with the front of the fixture at the right side of the
figure);

FIG. 11 is a right side elevation view of the second embodi-
ment (with the front of the fixture at the left side of the
figure);



FIG. 12 is a rear elevation view of the second embodiment;

FIG. 13 is a top plan view of the second embodiment (with
the front of the fixture at the bottom of the figure);

FIG. 14 is a bottom plan view of the second embodiment
(with the front of the fixture at the top of the figure); and,

FIG. 15 is a right-front perspective of a third embodiment of
a wall-mounted lighting fixture according to the invention as
seen from above having three vertically aligned units, with
units according to the first embodiment at the top and
bottom, and one unit according to the second embodiment in
the center.

1 Claim, 11 Drawing Sheets



US D566,878 S

Page 2

U.S. PATENT DOCUMENTS

3,121,817	A *	2/1964	Saviers	313/512	D312,319	S *	11/1990	Kunz	D26/72
D210,903	S *	4/1968	Dalton, Jr.	D26/122	D411,634	S *	6/1999	Connelly	D26/24
D282,687	S *	2/1986	McMahon	D26/139	D485,932	S *	1/2004	Crane	D26/76
						6,919,678	B2 *	7/2005	Ozolins et al.	313/479
						D519,667	S *	4/2006	Zucker	D26/85




FIG. 1




FIG. 3




FIG. 4




FIG. 5



FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 11




FIG. 12



FIG. 13



FIG. 14




FIG. 15