



US00D567641S

(12) **United States Design Patent**  
**Clarke**

(10) **Patent No.:** **US D567,641 S**

(45) **Date of Patent:** **\*\* Apr. 29, 2008**

(54) **WIRE TERMINATION, CONNECTING AND TENSIONING DEVICE**

7,168,992 B2 \* 1/2007 Vo et al. .... 439/676  
2002/0155745 A1 \* 10/2002 Vo et al. .... 439/352

(75) Inventor: **Neil Clarke**, Sheffield (GB)

\* cited by examiner

(73) Assignee: **Gripple Limited**, Sheffield (GB)

*Primary Examiner*—Holly H. Baynham

*Assistant Examiner*—Sheryl Friedman

(\*\*) Term: **14 Years**

(74) *Attorney, Agent, or Firm*—King & Schickli, PLLC

(21) Appl. No.: **29/250,171**

(57) **CLAIM**

(22) Filed: **Nov. 6, 2006**

The ornamental design of a wire termination, connecting and tensioning device, as shown and described.

(30) **Foreign Application Priority Data**

May 8, 2006 (EM) ..... 000526793-0001

**DESCRIPTION**

(51) **LOC (8) Cl.** ..... **08-08**

FIG. 1 is a view of the device from above one end and one side;

(52) **U.S. Cl.** ..... **D8/383**

FIG. 2 is a view from above and the other end and from the same side;

(58) **Field of Classification Search** ..... D8/382,  
D8/383; 439/404, 409, 410, 417, 369; 24/115 R  
See application file for complete search history.

FIG. 3 is an elevation of the same side of the device, the opposite side being mirror image;

(56) **References Cited**


**U.S. PATENT DOCUMENTS**

D247,345 S \* 2/1978 Mulholland ..... D8/383  
5,637,011 A \* 6/1997 Meyerhoefer et al. .... 439/409  
D499,330 S \* 12/2004 Peato ..... D8/383

FIG. 4 is an elevation of the device as seen from the left hand side of FIG. 3; the opposite side being a mirror image; and,

FIG. 5 is an elevation as seen from above FIG. 3.

**1 Claim, 5 Drawing Sheets**






FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5