



US00D567773S

(12) **United States Design Patent**
Kamada

(10) **Patent No.:** **US D567,773 S**
(45) **Date of Patent:** **** Apr. 29, 2008**

(54) **LIGHT EMITTING DIODE**

(75) Inventor: **Kazuhiro Kamada**, Tokushima (JP)

(73) Assignee: **Nichia Corporation**, Anan-shi (JP)

(**) Term: **14 Years**

(21) Appl. No.: **29/261,101**

(22) Filed: **Jun. 8, 2006**

(30) **Foreign Application Priority Data**

Jan. 31, 2006	(JP)	2006-001918
Jan. 31, 2006	(JP)	2006-001920
Jan. 31, 2006	(JP)	2006-001921
Jan. 31, 2006	(JP)	2006-001922
Jan. 31, 2006	(JP)	2006-001923

(51) **LOC (8) Cl.** **13-03**

(52) **U.S. Cl.** **D13/180**

(58) **Field of Classification Search** D13/180;
D26/2; 257/79, 80, 81, 88, 89, 95, 98, 99,
257/100; 313/483, 498, 500; 362/555, 800
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

D477,580	S *	7/2003	Kamada	D13/182
D503,690	S *	4/2005	Kamada	D13/180
D523,826	S *	6/2006	Kamada	D13/180
7,078,728	B2 *	7/2006	Ishii et al.	257/79
7,081,644	B2 *	7/2006	Flaherty et al.	257/98
D534,504	S *	1/2007	Kim et al.	D13/180
D542,743	S *	5/2007	Jung et al.	D13/180
2004/0041222	A1 *	3/2004	Loh	257/433
2004/0126913	A1 *	7/2004	Loh	438/26
2006/0267036	A1 *	11/2006	Lee et al.	257/98
2007/0029570	A1 *	2/2007	Shin et al.	257/99
2007/0063321	A1 *	3/2007	Han et al.	257/675
2007/0114559	A1 *	5/2007	Sayers et al.	257/100

FOREIGN PATENT DOCUMENTS

JP 1225893 S 12/2004

KR 30-0400598 12/2005

* cited by examiner

Primary Examiner—Selina Sikder

(74) *Attorney, Agent, or Firm*—Global IP Counselors, LLP

(57) **CLAIM**

The ornamental design for a light emitting diode, as shown and described.

DESCRIPTION

FIG. 1 is a front top side perspective view of a light emitting diode in accordance with a first embodiment of my new design;

FIG. 2 is a front bottom side perspective view of the light emitting diode in accordance with the first embodiment of my new design;

FIG. 3 is a rear side perspective view of the light emitting diode in accordance with the first embodiment of my new design;

FIG. 4 is a front elevational view of the light emitting diode in accordance with the first embodiment of my new design;

FIG. 5 is a rear elevational view of the light emitting diode in accordance with the first embodiment of my new design;

FIG. 6 is a top plan view of the light emitting diode in accordance with the first embodiment of my new design;

FIG. 7 is a bottom plan view of the light emitting diode in accordance with the first embodiment of my new design;

FIG. 8 is a right side end elevational view of the light emitting diode in accordance with the first embodiment of my new design;

FIG. 9 is a left side end elevational view of the light emitting diode in accordance with the first embodiment of my new design;

FIG. 10 is a front elevational view of the light emitting diode in accordance with the first embodiment of my new design with environment shown in broken lines;

FIG. 11 is a front top side perspective view of a light emitting diode in accordance with a second embodiment of my new design;





FIG. **12** is a front bottom side perspective view of the light emitting diode in accordance with the second embodiment of my new design;

FIG. **13** is a rear side perspective view of the light emitting diode in accordance with the second embodiment of my new design;

FIG. **14** is a front elevational view of the light emitting diode in accordance with the second embodiment of my new design;

FIG. **15** is a rear elevational view of the light emitting diode in accordance with the second embodiment of my new design;

FIG. **16** is a top plan view of the light emitting diode in accordance with the second embodiment of my new design;

FIG. **17** is a bottom plan view of the light emitting diode in accordance with the second embodiment of my new design;

FIG. **18** is a right side end elevational view of the light emitting diode in accordance with the second embodiment of my new design;

FIG. **19** is a left side end elevational view of the light emitting diode in accordance with the second embodiment of my new design; and,

FIG. **20** is a front elevational view of the light emitting diode in accordance with the second embodiment of my new design with environment shown in broken lines.

The broken line showing of environment (the remaining structure of the light emitting diode) in the Figures is for illustrative purposes only and forms no part of the claimed design.

The opaque line shading illustrates a translucent portion of the light emitting diode through which the environment shown in the broken lines may be visible as illustrated in FIGS. **10** and **20**.

1 Claim, 12 Drawing Sheets




Fig. 1




Fig. 2




Fig. 3




Fig. 4




Fig. 5




Fig. 6




Fig. 7




Fig. 8




Fig. 9




Fig. 10




Fig. 11




Fig. 12




Fig. 13




Fig. 14




Fig. 15




Fig. 16




Fig. 17




Fig. 18




Fig. 19




Fig. 20