



US00D568388S

(12) **United States Design Patent**
Hammad

(10) **Patent No.:** **US D568,388 S**
(45) **Date of Patent:** **** May 6, 2008**

(54) **ASYMMETRICAL CONTACTLESS DATA CARD WITH OFF-CENTER APERTURE**

(75) Inventor: **Ayman Hammad**, Pleasanton, CA (US)

(73) Assignee: **Visa U.S.A. Inc.**, San Francisco, CA (US)

(**) Term: **14 Years**

(21) Appl. No.: **29/263,220**

(22) Filed: **Jul. 17, 2006**

(51) **LOC (8) Cl.** **19-08**

(52) **U.S. Cl.** **D19/10; D14/436**

(58) **Field of Classification Search** D19/1-25,
D19/34.1-34.5, 35-42, 52; D3/207, 208,
D3/212, 215; D20/22, 24, 27, 28, 40-43;
40/1.5, 6, 27, 107, 119, 120, 124, 299, 358,
40/617, 634, 636, 60, 662; 281/15.1, 33,
281/38; 108/60, 61; 248/44.1, 316.5, 460;
229/74; 206/39.6; D11/79; D8/347; D14/356,
D14/434-438

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

938,310	A *	10/1909	Foster	40/662
2,211,556	A *	8/1940	Brell et al.	493/235
2,297,285	A *	9/1942	Bledsoe	40/634
3,423,861	A *	1/1969	Forsyth	40/662
3,727,333	A *	4/1973	Ward et al.	40/661.04
3,826,549	A *	7/1974	Scholfield	312/59
4,660,225	A *	4/1987	Kahn	2/49.4
4,817,691	A *	4/1989	Lau	141/390
4,877,950	A *	10/1989	Halpern	235/487
5,188,424	A *	2/1993	Herron	297/195.1
D345,686	S *	4/1994	Boehner	D8/347
D352,600	S *	11/1994	Steeley	D3/208
D357,114	S *	4/1995	MacDonald	D3/207

(Continued)

OTHER PUBLICATIONS

U.S. Appl. No. 29/263,226, Hammad.
U.S. Appl. No. 29/263,221, Hammad.
U.S. Appl. No. 29/269,954, Hammad.
U.S. Appl. No. 29/269,966, Law et al.
U.S. Appl. No. 29/266,546, Hammad.
U.S. Appl. No. 29/269,951, Law et al.
Color photograph of key fob design, 1 page.

Primary Examiner—Robert M. Spear
Assistant Examiner—Susan E Krakower

(74) *Attorney, Agent, or Firm*—Townsend and Townsend and Crew LLP

(57) **CLAIM**

The ornamental design for an asymmetrical contactless data card with off-center aperture, as shown and described.

DESCRIPTION

FIG. 1 is a perspective view of an asymmetrical contactless data card with off-center aperture according to a first embodiment of my new design;

FIG. 2 is a front elevation view thereof;

FIG. 3 is left side view elevation view thereof;

FIG. 4 is a right side elevation view thereof;

FIG. 5 is a rear elevational view thereof;

FIG. 6 is a top view thereof;

FIG. 7 is a bottom view thereof;

FIG. 8 is a perspective view of a second embodiment of my new design;

FIG. 9 is a front elevational view thereof;

FIG. 10 is a left side view elevation view thereof;


FIG. 11 is a right side elevation view thereof;

FIG. 12 is a rear elevation view thereof;

FIG. 13 is a top view thereof; and,

FIG. 14 is a bottom view thereof.

1 Claim, 4 Drawing Sheets



US D568,388 S

Page 2

U.S. PATENT DOCUMENTS

D377,313 S *	1/1997	Tipp	D9/434	6,594,154 B1 *	7/2003	Brewer et al.	361/801
D408,855 S *	4/1999	Ho	D19/52	D480,754 S *	10/2003	Berger	D19/1
D412,165 S *	7/1999	Niitsu	D14/435	D489,767 S *	5/2004	White	D20/42
D434,636 S *	12/2000	Van Den Acker	D8/347	D490,103 S *	5/2004	Rangel et al.	D19/10
D442,598 S *	5/2001	Wallace et al.	D14/436	D510,384 S *	10/2005	Allen et al.	D19/10
D447,481 S *	9/2001	Wallace et al.	D14/436	D534,414 S *	1/2007	Stifle et al.	D8/347
D453,515 S *	2/2002	Brewer et al.	D14/436				

* cited by examiner




FIG. 1




FIG. 3

FIG. 2

FIG. 4




FIG. 6




FIG. 5




FIG. 7




FIG. 8




FIG. 10

FIG. 9

FIG. 11




FIG. 13




FIG. 12



FIG. 14