



US00D568549S

(12) **United States Design Patent**  
**Augsten**

(10) **Patent No.:** **US D568,549 S**

(45) **Date of Patent:** **\*\* May 6, 2008**

(54) **RIDING STIRRUP**

(75) Inventor: **Christoph Andres Georg Augsten,**  
Köln (DE)

(73) Assignee: **Stubben Steel Tec GmbH,** Stans (CH)

(\*\*) Term: **14 Years**

(21) Appl. No.: **29/267,812**

(22) Filed: **Oct. 23, 2006**

(30) **Foreign Application Priority Data**

Aug. 9, 2006 (EM) ..... 000572722

(51) **LOC (8) Cl.** ..... **30-04**

(52) **U.S. Cl.** ..... **D30/142**

(58) **Field of Classification Search** ..... D30/142,  
D30/146; 54/47-49.1; 119/850  
See application file for complete search history.

(56) **References Cited**

**U.S. PATENT DOCUMENTS**

|           |     |         |                 |         |
|-----------|-----|---------|-----------------|---------|
| 4,577     | A * | 6/1846  | Parrling        | 54/49   |
| 50,007    | A * | 9/1865  | Irion           | 54/49   |
| 83,450    | A * | 10/1868 | Bond            | 54/49   |
| 222,155   | A * | 12/1879 | Pulliam         | 54/49   |
| 222,556   | A * | 12/1879 | Whitman         | 54/47   |
| 223,577   | A * | 1/1880  | Brower          | 54/47   |
| RE9,609   | E * | 3/1881  | Brower          | 54/47   |
| 376,526   | A * | 1/1888  | Jennings et al. | 54/47   |
| 437,108   | A * | 9/1890  | Goodridge       | 54/49   |
| 792,228   | A * | 6/1905  | Mills           | 54/47   |
| 1,088,552 | A * | 2/1914  | Dolan           | 54/49   |
| 1,639,073 | A * | 8/1927  | Berbaum         | 54/47   |
| 2,098,141 | A * | 11/1937 | Galbreath       | 54/48   |
| 2,187,983 | A * | 1/1940  | Moore           | 54/47   |
| 3,905,179 | A * | 9/1975  | Bischeltsrieder | 54/47   |
| 3,910,015 | A * | 10/1975 | Ebejer          | 54/49   |
| 4,587,798 | A * | 5/1986  | Taylor          | 54/49   |
| 5,172,538 | A * | 12/1992 | Luger           | 54/47   |
| D339,665  | S * | 9/1993  | Nishimoula      | D30/142 |
| D383,572  | S * | 9/1997  | Rea             | D30/142 |

|              |      |         |                  |         |
|--------------|------|---------|------------------|---------|
| D411,667     | S *  | 6/1999  | Martin           | D30/142 |
| 5,930,986    | A *  | 8/1999  | Meaghan et al.   | 54/47   |
| 5,979,149    | A *  | 11/1999 | Martin           | 54/49   |
| 6,062,007    | A *  | 5/2000  | Cargill          | 54/47   |
| 6,089,004    | A *  | 7/2000  | Hsi-Chang et al. | 54/49   |
| 6,330,781    | B1 * | 12/2001 | Meroth           | 54/49   |
| D461,602     | S *  | 8/2002  | Abady            | D30/142 |
| D491,698     | S *  | 6/2004  | Zucchini         | D30/142 |
| 6,865,867    | B1 * | 3/2005  | Zucchini         | 54/47   |
| 2001/0045084 | A1 * | 11/2001 | Vollmecke et al. | 54/47   |
| 2005/0076620 | A1 * | 4/2005  | Sjosward         | 54/48   |
| 2005/0081493 | A1 * | 4/2005  | Chang            | 54/48   |

\* cited by examiner

*Primary Examiner*—Melanie Tung

*Assistant Examiner*—Susan Moon Lee

(74) *Attorney, Agent, or Firm*—Head, Johnson & Kachigian

(57) **CLAIM**

The ornamental design for a riding stirrup, as shown and described.

**DESCRIPTION**

FIG. 1 is a left side view of a riding stirrup constructed in accordance with the present invention;

FIG. 2 is a front view of the riding stirrup as shown in FIG. 1;

FIG. 3 is a top view of the riding stirrup as shown in FIG. 1; and,


FIG. 4 is a bottom view of the riding stirrup as shown in FIG. 1.

The right side view is a mirror image of the left side view shown in FIG. 1; and,

The rear view is a mirror image of the front view shown in FIG. 2.

The broken line showing of the bottom of the riding stirrup in FIG. 2 illustrates the moveability of the lower portion of the stirrup into an alternate position.

**1 Claim, 2 Drawing Sheets**






FIG. 2




FIG. 1




FIG. 3




FIG. 4