

US00D568914S

(12) **United States Design Patent**
Or et al.

(10) **Patent No.:** **US D568,914 S**

(45) **Date of Patent:** **** May 13, 2008**

- (54) **SUBSTRATE SUPPORT LIFT PIN**
- (75) Inventors: **David T. Or**, San Jose, CA (US); **Keith K. Koai**, Los Gatos, CA (US); **Hiroyuki Takahama**, Sawara (JP); **Takahiro Ito**, Urayasu (JP); **Koji Ota**, Chiba (JP); **Hiroshi Sato**, Chiba (JP)
- (73) Assignee: **Applied Materials, Inc.**, Santa Clara, CA (US)
- (**) Term: **14 Years**
- (21) Appl. No.: **29/256,744**
- (22) Filed: **Mar. 24, 2006**

EP	0 592 017	4/1994
EP	1 202 330	5/2002
JP	07 176472	7/1995

OTHER PUBLICATIONS

PCT International Search Report for PCT/US04/007164, Dated Apr. 18, 2005.

PCT Written Opinion for PCT/US04/007164, Dated Apr. 18, 2005.

Primary Examiner—Antoine D. Davis

Assistant Examiner—Patricia Palasik

(74) *Attorney, Agent, or Firm*—Patterson & Sheridan, LLP

Related U.S. Application Data

- (63) Continuation of application No. 11/120,456, filed on May 3, 2005, which is a continuation of application No. 10/241,005, filed on Sep. 10, 2002, now Pat. No. 6,887,317.

- (51) **LOC (8) Cl.** **15-09**
- (52) **U.S. Cl.** **D15/138**
- (58) **Field of Classification Search** D8/387;
D15/122, 138, 140, 199; 118/500, 728, 729;
156/345.51–345.55

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

4,289,522	A *	9/1981	Bailey et al.	118/729
5,762,544	A	6/1998	Zuniga et al.	
5,796,066	A	8/1998	Guyot	
5,848,670	A	12/1998	Salzman	
5,879,128	A	3/1999	Tietz et al.	
5,900,062	A	5/1999	Loewenhardt et al.	
6,120,609	A	9/2000	Selyutin et al.	
6,146,504	A	11/2000	Patadia et al.	

(Continued)

FOREIGN PATENT DOCUMENTS

EP	0 284 343	9/1988
----	-----------	--------

(57) **CLAIM**

The ornamental design for a substrate support lift pin, as shown and described.

DESCRIPTION


A lift pin for selectively spacing a substrate from a substrate support is provided. Embodiments of the lift pin include a lift pin shaft and at least one larger diameter shoulder section symmetrical the lift pin shaft that forms a relief region between the lift pin and a guide hole disposed through a substrate support. The shoulder section reduces pin scratching, particle generation, and component wear, thus increasing the life of the lift pin. The shoulder section also minimizes sticking of the lift pin, thus enhancing movement of the lift pin through the guide hole. The shoulder section may be made of a different material than the lift pin shaft and/or an outer surface of the shoulder section may be machined to a micro-smooth surface. An upper portion of the lift pin also includes a tapered portion configured to provide a stop for the lift pin to prevent the lift pin from falling through the guide hole in the substrate support.

FIG. 1 is a schematic side view of one embodiment of a lift pin.

FIG. 2 is a top view of FIG. 1; and,

FIG. 3 is a cross-sectional view taken along line 3—3 of FIG. 1.

1 Claim, 1 Drawing Sheet



US D568,914 S

Page 2

U.S. PATENT DOCUMENTS

D469,007 S	1/2003	Chen et al.	2002/0121312 A1	9/2002	Lubomirsky et al.	
6,511,368 B1	1/2003	Halley	2003/0075387 A1	4/2003	Wang et al.	
D502,644 S	3/2005	Ellis et al.	2003/0205329 A1*	11/2003	Gujer et al.	156/345.51
D504,313 S *	4/2005	Stoewer et al.	2004/0045509 A1*	3/2004	Or et al.	118/729
D506,922 S	7/2005	Simon	2004/0219006 A1*	11/2004	Tran et al.	187/250
6,887,317 B2*	5/2005	Or et al.	2005/0194100 A1*	9/2005	Or et al.	156/345.51
D506,922 S	7/2005	Simon	2007/0131173 A1*	6/2007	Halpin et al.	118/728
6,958,098 B2*	10/2005	Gujer et al.	2007/0157466 A1*	7/2007	Kida et al.	118/728
7,204,888 B2*	4/2007	Tran et al.				
2002/0011204 A1	1/2002	Gujer et al.				

* cited by examiner




FIG. 1




FIG. 2



FIG. 3