



US00D569424S

(12) **United States Design Patent**
Law et al.

(10) **Patent No.:** **US D569,424 S**

(45) **Date of Patent:** **** May 20, 2008**

- (54) **PORTABLE DATA DEVICE WITH EXTERNAL APERTURE**
- (75) Inventors: **Christopher Law**, Pelham Manor, NY (US); **Vlad Guzner**, Brooklyn, NY (US); **Maorong Lin**, Brooklyn, NY (US); **David Sohn**, Fort Lee, NJ (US)
- (73) Assignee: **Visa U.S.A. Inc.**, San Francisco, CA (US)

(**) **Term:** **14 Years**

(21) **Appl. No.:** **29/269,950**

(22) **Filed:** **Dec. 11, 2006**

(51) **LOC (8) Cl.** **19-08**

(52) **U.S. Cl.** **D19/10; D14/436**

(58) **Field of Classification Search** D19/1–25, D19/34.1–34.5, 35–42, 52; D3/207, 208, D3/212, 215; D20/22, 24, 27, 28, 40–43; 40/1.5, 6, 27, 107, 119, 120, 124, 299, 358, 40/617, 634, 636, 60, 662; 281/15.1, 33, 281/38; 108/60, 61; 248/44.1, 316.5, 460; 229/74; 206/39.6; D11/79; D8/347; D14/356, D14/434–438

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

D181,830 S *	1/1958	Amburgh	D20/22
D213,989 S *	4/1969	Boone	D7/698
D278,363 S *	4/1985	Schenkel et al.	D24/189
5,188,424 A *	2/1993	Herron	297/195.1
D340,742 S *	10/1993	Alfa	D19/36
D359,645 S *	6/1995	Luccisano	D6/601
D361,347 S *	8/1995	Adler	D19/52
5,484,637 A *	1/1996	Paragon et al.	428/66.6
5,551,593 A *	9/1996	Wiens	220/575
D408,056 S *	4/1999	Broyles	D19/35
D409,655 S *	5/1999	Broyles	D19/35
D429,282 S *	8/2000	Velazquez et al.	D20/11
D447,332 S *	9/2001	Pisarevsky	D3/207
D453,797 S *	2/2002	Cranston et al.	D20/23
D463,104 S *	9/2002	Ames	D3/207

D498,761 S *	11/2004	Hart et al.	D14/436
D499,101 S *	11/2004	Hart et al.	D14/436
D500,808 S *	1/2005	Howard	D20/28
D517,603 S *	3/2006	Johnson	D19/26
D527,056 S *	8/2006	Manville	D21/484
D553,195 S *	10/2007	Chamberlain	D20/29

* cited by examiner

Primary Examiner—Robert M. Spear

Assistant Examiner—Susan E Krakower

(74) *Attorney, Agent, or Firm*—Townsend and Townsend and Crew LLP

(57) **CLAIM**

The ornamental design for a portable data device with external aperture, as shown and described.

DESCRIPTION

FIG. 1 is a perspective view of a first embodiment of a portable data device with external aperture showing my new design;

FIG. 2 is a top plan view thereof;

FIG. 3 is a left side elevation view thereof;

FIG. 4 is a right side elevation view thereof;

FIG. 5 is a bottom plan view thereof;

FIG. 6 is a front elevation view thereof;

FIG. 7 is a rear elevation view thereof;

FIG. 8 is a perspective view of a second embodiment of the portable data device with external aperture showing my new design;

FIG. 9 is a top plan view thereof;

FIG. 10 is a left side elevation view thereof;

FIG. 11 is a right side elevation view thereof;



FIG. 12 is a bottom plan view thereof;

FIG. 13 is a front elevation view thereof;

FIG. 14 is a rear elevation view thereof; and,

FIG. 15 is a cross-sectional view thereof along line 15—15 of FIG. 12.

1 Claim, 4 Drawing Sheets






FIG. 1




FIG. 3

FIG. 2

FIG. 4



FIG. 6




FIG. 5




FIG. 7




FIG. 8




FIG. 10

FIG. 9

FIG. 11



FIG. 13




FIG. 12



FIG. 14



FIG. 15