

US00D569790S

(12) **United States Design Patent** (10) **Patent No.:** **US D569,790 S**  
**Rumbarger et al.** (45) **Date of Patent:** **\*\* May 27, 2008**

(54) **TIRE**

(75) Inventors: **Jill Elizabeth Rumbarger**, Brighton, MI (US); **Paul Bryan Maxwell**, Kent, OH (US)

(73) Assignee: **The Goodyear Tire & Rubber Company**, Akron, OH (US)

(\*\*) Term: **14 Years**

(21) Appl. No.: **29/284,965**

(22) Filed: **Sep. 19, 2007**

(51) **LOC (8) Cl.** ..... **12-15**

(52) **U.S. Cl.** ..... **D12/579**

(58) **Field of Classification Search** ..... D12/544,  
D12/546, 560-561, 566-567, 579-581, 596-597,  
D12/602-603, 900-901, 594; 152/209.1,  
152/209.9-209.13, 209.18, 209.25, 209.28,  
152/455

See application file for complete search history.

(56) **References Cited**

**U.S. PATENT DOCUMENTS**

|            |   |         |                |       |         |
|------------|---|---------|----------------|-------|---------|
| D250,812 S | * | 1/1979  | Duncan         | ..... | D12/594 |
| D313,386 S |   | 1/1991  | Goto et al.    | ..... | D12/147 |
| D412,475 S | * | 8/1999  | Maxwell et al. | ..... | D12/579 |
| D440,911 S |   | 4/2001  | Slingluff      | ..... | D12/139 |
| D444,108 S | * | 6/2001  | Maxwell        | ..... | D12/579 |
| D456,343 S |   | 4/2002  | Allison        | ..... | D12/579 |
| D488,430 S | * | 4/2004  | Maxwell        | ..... | D12/544 |
| D492,644 S | * | 7/2004  | Maxwell        | ..... | D12/579 |
| D492,931 S |   | 7/2004  | Maxwell et al. | ..... | D12/579 |
| D496,324 S | * | 9/2004  | Graas et al.   | ..... | D12/546 |
| D496,328 S |   | 9/2004  | Shondel et al. | ..... | D12/579 |
| D529,860 S |   | 10/2006 | Shondel        | ..... | D12/512 |
| D536,661 S | * | 2/2007  | Maxwell        | ..... | D12/579 |

D558,134 S \* 12/2007 Graas et al. .... D12/544

\* cited by examiner

*Primary Examiner*—Stacia Cadmus

(74) *Attorney, Agent, or Firm*—Richard B. O'Planick

(57) **CLAIM**

The ornamental design for a tire, as shown and described.

**DESCRIPTION**

FIG. 1 is a perspective view of a tire showing our new design, it being understood that the pattern repeats uniformly throughout the circumference of the tread;

FIG. 2 is a front elevational view thereof;

FIG. 3 is a right side elevational view thereof; the other side being a mirror image thereof;

FIG. 4 is an enlarged fragmentary front elevational view thereof;


FIG. 5 is a perspective view of a second embodiment of a tire showing our new design, it being understood that the pattern repeats uniformly throughout the circumference of the tread and that the opposite side perspective view is a mirror image thereof; and,

FIG. 6 is a front elevational view of a second embodiment, it being understood that an enlarged fragmentary view thereof would be substantially identical to that shown in FIG. 4, with the exception of the inclusion of the sidewall in solid lines.

In the drawings the broken lines defining the sidewall, inner bead and the peripheral boundary between the tire tread and the sidewall in FIGS. 1 through 4 are for illustrative purposes only and form no part of the claimed design.

The dark stippled surface shading represents the recessed portion of the tread grooves having a depth as best shown in FIG. 2.

**1 Claim, 6 Drawing Sheets**








FIG-1






FIG-2






FIG-3






FIG-4





FIG-5






FIG-6