



US00D571187S

(12) **United States Design Patent**
Garnett

(10) **Patent No.:** **US D571,187 S**

(45) **Date of Patent:** **** Jun. 17, 2008**

(54) **TRIGGER LOCK**

(76) Inventor: **Vincent Garnett**, 1018 Jersey Ave., St. Cloud, FL (US) 34769

(**) Term: **14 Years**

(21) Appl. No.: **29/265,573**

(22) Filed: **Sep. 1, 2006**

(51) **LOC (8) Cl.** **08-07**

(52) **U.S. Cl.** **D8/333**

(58) **Field of Classification Search** D8/330-348;
70/14-16, 18, 30, 49; 150/101; 42/69.01,
42/70.07, 70.11; D22/108

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

| | | | | |
|-----------|-----|---------|-----------------|---------|
| 1,711,082 | A * | 4/1929 | Brite | 70/18 |
| D236,581 | S * | 9/1975 | Reisner | D8/333 |
| 4,175,595 | A | 11/1979 | Noe | 141/1 |
| D254,050 | S | 1/1980 | Fitzgerald | D8/349 |
| D254,837 | S | 4/1980 | Breaux | D8/349 |
| 4,200,943 | A | 5/1980 | Fredin et al. | 7/100 |
| 4,216,807 | A | 8/1980 | Diamond | 141/392 |
| 4,275,776 | A | 6/1981 | Rehkopf | 141/392 |
| 4,334,560 | A | 6/1982 | Lockwood | 141/392 |
| 4,337,917 | A | 7/1982 | Tesack et al. | 251/90 |
| 4,722,375 | A | 2/1988 | Fox | 141/392 |
| D315,287 | S * | 3/1991 | Lambert | D8/333 |
| 5,118,074 | A | 6/1992 | Weissman | 251/90 |
| 5,199,474 | A | 4/1993 | D'Angelo | 141/392 |
| 5,240,226 | A | 8/1993 | Bobst | 251/90 |
| 5,517,732 | A | 5/1996 | Crear | 24/299 |
| D371,292 | S * | 7/1996 | Baker | D8/333 |
| D415,009 | S * | 10/1999 | Hasselbusch | D8/331 |
| D537,143 | S * | 2/2007 | Fachione et al. | D22/108 |

* cited by examiner

Primary Examiner—Mitchell Siegel

(74) *Attorney, Agent, or Firm*—Brian S. Steinberger; Law Offices of Brian S. Steinberger, P.A.

(57) **CLAIM**

The ornamental design for a trigger lock, as shown and described.

DESCRIPTION

FIG. 1 is an upper side right perspective view of a novel trigger lock design with strap.

FIG. 2 is a lower side right perspective view of the design of FIG. 1.

FIG. 3 is a side planar view of the design of FIG. 1.

FIG. 4 is a top planar view of the design of FIG. 1.

FIG. 5 is a bottom planar view of the design of FIG. 1.

FIG. 6 is a rear view of the design of FIG. 1 without the strap.

FIG. 7 is a front view of the design of FIG. 1 without the strap.

FIG. 8 is another upper side right perspective view of a novel trigger lock design.

FIG. 9 is a lower side right perspective view of the design of FIG. 8.


FIG. 10 is a side planar view of the design of FIG. 8.

FIG. 11 is a top planar view of the design of FIG. 1; and,

FIG. 12 is a bottom planar view of the design of FIG. 1.

The broken lines showing of a connection ring in FIGS. 8-12 are for illustrative purposes and form no part of the claimed design, and the broken lines showing a strap in FIGS. 8-12 are for illustrative purposes and form no part of the claimed design.

1 Claim, 11 Drawing Sheets






Fig. 1




Fig. 2




Fig. 3




Fig. 4




Fig. 5





Fig. 6

Fig. 7






Fig. 8




Fig. 9




Fig. 10




Fig. 11




Fig. 12