

US00D571938S

(12) **United States Design Patent**
Uemoto et al.

(10) **Patent No.:** **US D571,938 S**
(45) **Date of Patent:** **** Jun. 24, 2008**

- (54) **LIGHTING APPARATUS**
- (75) Inventors: **Takaari Uemoto**, Kadoma (JP); **Keiji Nishimoto**, Kadoma (JP); **Yasuharu Ueno**, Kadoma (JP); **Satoshi Shida**, Kadoma (JP); **Yuji Omata**, Kadoma (JP)
- (73) Assignee: **Matsushita Electric Industrial Co., Ltd.**, Osaka (JP)
- (**) Term: **14 Years**
- (21) Appl. No.: **29/299,099**
- (22) Filed: **Dec. 19, 2007**

Related U.S. Application Data

- (62) Division of application No. 29/270,332, filed on Dec. 19, 2006.

(30) **Foreign Application Priority Data**

Jun. 20, 2006	(JP)	2006-15955
Jun. 20, 2007	(JP)	2006-15953

- (51) **LOC (8) Cl.** **26-04**
- (52) **U.S. Cl.** **D26/24; D26/1**
- (58) **Field of Classification Search** D26/24, D26/1, 2, 37, 72, 74, 80, 81, 83, 93, 105, D26/113, 25; D13/180, 182; 362/612, 631, 362/555, 89, 147, 153, 257, 800; 257/79, 257/80, 82, 88, 433; 313/500
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

D374,737 S *	10/1996	Can	D26/80
D477,093 S *	7/2003	Moriyama et al.	D26/3
D477,094 S *	7/2003	Moriyama et al.	D26/3
6,627,994 B2 *	9/2003	Hashimoto	257/739
D506,274 S *	6/2005	Moriyama et al.	D26/3
D513,082 S *	12/2005	Hoshikawa et al.	D26/25
D530,288 S *	10/2006	Nagai	D13/180
D531,139 S *	10/2006	Egawa et al.	D13/180
D532,544 S *	11/2006	Woertler	D26/80
D535,262 S *	1/2007	Saito et al.	D13/180
D541,761 S *	5/2007	Saito et al.	D13/180

D546,985 S *	7/2007	Hoshikawa et al.	D26/25
D552,566 S *	10/2007	Moriyama	D13/182
D560,293 S *	1/2008	Uemoto et al.	D26/37

FOREIGN PATENT DOCUMENTS

JP	2003-124528	4/2003
----	-------------	--------

OTHER PUBLICATIONS

Uemoto et al., U.S. Design Application entitled "Lighting Apparatus", U.S. Appl. No. 29/270,337, filed Dec. 19, 2006.

* cited by examiner

Primary Examiner—Cathron Brooks

Assistant Examiner—Angela J Lee

(74) *Attorney, Agent, or Firm*—Brinks Hofer Gilson & Lione

(57) **CLAIM**

The ornamental design for a lighting apparatus, as shown and described.

DESCRIPTION

FIG. 1 is a top perspective view of a lighting apparatus of the present invention;

FIG. 2 is a front view thereof, the rear view being a mirror image thereof;

FIG. 3 is a left side view thereof, the right side view being a mirror image thereof;

FIG. 4 is a top view thereof;


FIG. 5 is a bottom view thereof; and,

FIG. 6 is a partial cross-sectional view thereof taken along line 6—6 of FIG. 4.

Elongated elevations on a substrate are transparent and thus light comes through. Each elevation has a plate therein which has recesses in each of which a light source, such as an LED, is placed. The squares are electrodes.

Since all the elevations have the identical cross-sectional view, the cross-sectional view shown in FIG. 6 is taken from only one of the elevations.

1 Claim, 3 Drawing Sheets






FIG. 1




FIG. 2



FIG.3




FIG.4




FIG. 5




FIG. 6