US00D574316S

(12) United States Design Patent

Neidert et al.

(10) Patent No.: US D574,316 S
(45) Date of Patent: ** Aug. 5, 2008

(54) **TIRE**

(75) Inventors: **Matthew John Neidert**, Akron, OH (US); **Shannon Joseph Hughes**, Rootstown, OH (US); **Charles Joseph Ashton**, Cuyahoga Falls, OH (US); **Brian David Holden**, Kent, OH (US); **Karl Eric Sundkvist**, Akron, OH (US); **Kevin Lee Burnworth**, Cuyahoga Falls, OH (US); **Jonathan James Shondel**, Massillon, OH (US); **Travis Lynn Hollabaugh**, Canton, OH (US)

(73) Assignee: **The Goodyear Tire & Rubber Company**, Akron, OH (US)

(**) Term: **14 Years**

(21) Appl. No.: **29/296,118**

(22) Filed: **Oct. 15, 2007**

(51) **LOC (8) Cl.** **12-15**
(52) **U.S. Cl.** **D12/514**; D12/531
(58) **Field of Classification Search** D12/505–532, D12/900–901; 152/209.1, 209.8–209.13, 152/209.25, 209.28, 455
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

D340,212	S		10/1993	Montag et al.	D12/147
D358,793	S	*	5/1995	Himuro et al.	D12/530
D382,522	S	*	8/1997	Ratliff, Jr.	D12/514
D394,032	S		5/1998	Maxwell	D12/147
D408,000	S	*	4/1999	Otani et al.	D12/532
D409,959	S		5/1999	Maxwell	D12/147
D456,762	S	*	5/2002	Graas	D12/524
D471,152	S		3/2003	Graas et al.	D12/563
D473,842	S	*	4/2003	Ratliff, Jr.	D12/514
D484,845	S	*	1/2004	Takahashi et al.	D12/531
D491,130	S		6/2004	Welbes	D12/563
D491,134	S		6/2004	Brayer et al.	D12/588
D495,990	S		9/2004	Graas	D12/563
D504,107	S		4/2005	Matsumoto et al.	D12/563
D504,386	S	*	4/2005	Seifert	D12/532
D509,786	S		9/2005	Matsumoto et al.	D12/563
D515,022	S	*	2/2006	Helt et al.	D12/528
D516,998	S		3/2006	Wang et al.	D12/563
D525,579	S	*	7/2006	Graas	D12/514
D529,861	S	*	10/2006	Takahashi et al.	D12/531
D547,716	S		7/2007	Ochi	D12/518
D551,157	S	*	9/2007	Shondel	D12/524

* cited by examiner

Primary Examiner—Stacia Cadmus
(74) *Attorney, Agent, or Firm*—Richard B. O'Planick

(57) **CLAIM**

The ornamental design for a tire, as shown and described.

DESCRIPTION

FIG. **1** is a perspective view of a tire showing our new design, it being understood that the pattern repeats uniformly throughout the circumference of the tread;

FIG. **2** is a front elevational view thereof;

FIG. **3** is a right side elevational view thereof;

FIG. **4** is a left side elevational view thereof;

FIG. **5** is an enlarged fragmentary front elevational view thereof;

FIG. **6** is a perspective view of a second embodiment of a tire showing our new design, it being understood that the pattern repeats uniformly throughout the circumference of the tread and that the opposite side perspective view would be substantially identical to that as shown in FIGS. **2** and **4**; and,

FIG. **7** is a front elevational view of a second embodiment, it being understood that an enlarged fragmentary view thereof would be substantially identical to that shown in FIG. **5**, with the exception of the inclusion of the sidewall in solid lines.

In the drawings the broken lines defining the sidewall, inner bead and the peripheral boundary between the tire tread and the sidewall in FIGS. **1** through **4** are for illustrative purposes only and form no part of the claimed design.

1 Claim, 7 Drawing Sheets





FIG-1



FIG-2



FIG-3



FIG-4



FIG-5



FIG-6



FIG-7