



US00D574984S

(12) **United States Design Patent**  
**Hesse et al.**

(10) **Patent No.:** **US D574,984 S**

(45) **Date of Patent:** **\*\* Aug. 12, 2008**

(54) **PORTION OF A FLASHLIGHT**

(75) Inventors: **Bryan L. Hesse**, Guilford, CT (US);  
**James Sener**, Glastonbury, CT (US);  
**Kevin S. Garrity**, Madison, CT (US)

(73) Assignee: **The Gillette Company**, Boston, MA  
(US)

(\*\*) Term: **14 Years**

(21) Appl. No.: **29/296,222**

(22) Filed: **Oct. 16, 2007**

(51) **LOC (8) Cl.** ..... **26-02**

(52) **U.S. Cl.** ..... **D26/37**

(58) **Field of Classification Search** ..... D26/37-50;  
362/157, 158, 171-174, 183-208

See application file for complete search history.

(56) **References Cited**

**U.S. PATENT DOCUMENTS**

D544,621 S \* 6/2007 Kim ..... D26/37  
D549,369 S \* 8/2007 DeBrunner ..... D26/37  
D551,366 S \* 9/2007 Galli ..... D26/37

**OTHER PUBLICATIONS**

Hesse et al., U.S. Appl. No. 29/296,228, filed Oct. 16, 2007, entitled  
"Flashlight".

Hesse et al., U.S. Appl. No. 29/296,218, filed Oct. 16, 2007, entitled  
"Flashlight".

Hesse et al., U.S. Appl. No. 29/292,537, filed Oct. 16, 2007, entitled  
"Flashlight".

\* cited by examiner

*Primary Examiner*—Marcus A. Jackson

(74) *Attorney, Agent, or Firm*—Fish & Richardson P.C.

(57) **CLAIM**

The ornamental design for a portion of a flashlight, as shown  
and described.

**DESCRIPTION**

FIG. 1 is a perspective view of a portion of a flashlight as seen  
from the front, top, right side;

FIG. 2 is a perspective view of a portion of a flashlight of FIG.  
1 as seen from the rear, top, left side; and,


FIG. 3 is an enlarged perspective view of a portion of a  
flashlight of FIG. 1 showing parts of the design at a larger  
scale.


The broken lines which define the bounds of the claimed  
design form no part thereof. The broken lines showing the  
remainder of the flashlight are for illustrative purposes only  
and form no part of the claimed design.

In other embodiments, the ornamental features illustrated in  
the Figures extend around the entire circumference of the  
flashlight.

In other embodiments, the flashlight includes flared front and  
rear end portion shown in broken lines in the Figures, i.e., the  
rear end portion defining the flare optionally is shown in solid  
lines.


**1 Claim, 3 Drawing Sheets**





**FIG. 1**

**FIG. 2**



**FIG. 3**

