



US00D575264S

(12) **United States Design Patent**
Nakajima

(10) **Patent No.:** **US D575,264 S**

(45) **Date of Patent:** **** Aug. 19, 2008**

(54) **VOICE RECORDING/REPRODUCING
DEVICE**

(75) Inventor: **Kenzo Nakajima**, Hachioji (JP)

(73) Assignee: **Olympus Imaging Corp.**, Tokyo (JP)

(**) Term: **14 Years**

(21) Appl. No.: **29/270,717**

(22) Filed: **Dec. 29, 2006**

(30) **Foreign Application Priority Data**

Dec. 12, 2006 (JP) 2006-034155
Dec. 12, 2006 (JP) 2006-034156

(51) **LOC (8) Cl.** **14-01**

(52) **U.S. Cl.** **D14/167**

(58) **Field of Classification Search** D14/167,
D14/154, 168, 188, 496, 156, 160, 161, 162,
D14/163, 164, 165, 192; D16/208; D26/38;
455/351, 350

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

D264,332 S * 5/1982 Nakayama D14/165
D278,899 S * 5/1985 Takata D14/165
D385,274 S * 10/1997 Shimobayashi D14/154
D419,464 S * 1/2000 Chang D10/78
D427,176 S * 6/2000 Obata D14/167
D430,134 S * 8/2000 Obata et al. D14/165
D436,941 S * 1/2001 Kataoka D14/165
D438,857 S * 3/2001 Ishii D14/161
D450,309 S * 11/2001 Ishii et al. D14/167
D459,714 S * 7/2002 Suzuki et al. D14/165
D463,393 S * 9/2002 Kataoka D14/167
D473,207 S * 4/2003 Tanio D14/168
D473,535 S * 4/2003 Ishii D14/167

D484,482 S * 12/2003 Tanio D14/167
D507,557 S * 7/2005 Meguro D14/167
D508,906 S * 8/2005 Tajima D14/167
D510,334 S * 10/2005 Isono D14/167
D517,522 S * 3/2006 Tajima D14/167
D533,861 S * 12/2006 Amano D14/167
D533,862 S * 12/2006 Jinde D14/167
2005/0224332 A1 * 10/2005 Yamaguchi 200/547

* cited by examiner

Primary Examiner—Cathron C. Brooks

Assistant Examiner—Austin Murphy

(74) *Attorney, Agent, or Firm*—Straub and Pokotylo; John C. Pokotylo

(57) **CLAIM**

The ornamental device for a voice recording/reproducing device, as shown and described.

DESCRIPTION

An indicator which emits light at the time of recording or the like is provided at the center in a horizontally extending slit formed near the top in each of the front surface and the rear surface. Openings for a microphone are provided respectively at the left side and at the right side of the slit and at the front surface side and the rear surface side of the slit:

FIG. 1 is a front, top and right side perspective view of a voice recording/reproducing device showing my new design in accordance with the first embodiment;

FIG. 2 is a front elevational view thereof;

FIG. 3 is a rear elevational view thereof;

FIG. 4 is a top plan view thereof;

FIG. 5 is a bottom plan view thereof;

FIG. 6 is a left side elevational view thereof; and,

FIG. 7 is a right side elevational view thereof.

1 Claim, 5 Drawing Sheets




FIG. 1




FIG. 2




FIG. 3




FIG.4




FIG.5




FIG.6




FIG.7

