



US00D576517S

(12) **United States Design Patent**
Kawaguchi

(10) **Patent No.:** **US D576,517 S**

(45) **Date of Patent:** **** Sep. 9, 2008**

(54) **BUCKLE**

D502,670 S * 3/2005 Yoshiguchi D11/216
D502,671 S * 3/2005 Yoshiguchi D11/216
D535,913 S * 1/2007 Yang D11/216

(75) Inventor: **Gaku Kawaguchi**, Yokohama (JP)

* cited by examiner

(73) Assignee: **Nifco Inc.**, Yokohama-shi, Kanagawa (JP)

Primary Examiner—R. Seifert

(**) Term: **14 Years**

(74) *Attorney, Agent, or Firm*—Manabu Kanesaka

(21) Appl. No.: **29/290,817**

(57) **CLAIM**

(22) Filed: **Jan. 17, 2008**

The ornamental design for a buckle, as shown and described.

(30) **Foreign Application Priority Data**

DESCRIPTION

Jul. 25, 2007 (JP) 2007-020080

FIG. 1 is a perspective view of a buckle showing my new design;

(51) **LOC (8) Cl.** **02-07**

FIG. 2 is a front view thereof; a rear view being the same as the front view;

(52) **U.S. Cl.** **D11/216**

FIG. 3 is a plan view thereof;

(58) **Field of Classification Search** D11/1-2,
D11/86, 87, 200-201, 206-210, 212-216,
D11/218; 24/163 R, 169-171, 173, 177-179,
24/191, 194-195, 197, 200, 303

FIG. 4 is a bottom view thereof;

See application file for complete search history.

FIG. 5 is a right side view thereof; a left side view being the same as the right side view;

(56) **References Cited**

FIG. 6 is a sectional view thereof taken along line 6-6 in FIG. 5; and,

U.S. PATENT DOCUMENTS

FIG. 7 is another sectional view thereof taken along line 7-7 in FIG. 2.

D423,985 S * 5/2000 Yoshiguchi D11/218
D479,486 S * 9/2003 Uehara et al. D11/216

1 Claim, 3 Drawing Sheets




Fig. 1




Fig. 2




Fig. 3




Fig. 4




Fig. 5




Fig. 6




Fig. 7

