



US00D576753S

(12) **United States Design Patent**
Mukai

(10) **Patent No.:** **US D576,753 S**
(45) **Date of Patent:** **** Sep. 9, 2008**

(54) **LIGHTING FIXTURE WITH LIGHT
EMITTING DIODE**

(75) Inventor: **Kenji Mukai**, Shijonawate (JP)

(73) Assignee: **Matsushita Electric Industrial Co.,
Ltd.**, Osaka (JP)

(**) Term: **14 Years**

(21) Appl. No.: **29/297,391**

(22) Filed: **Nov. 9, 2007**

Related U.S. Application Data

(62) Division of application No. 29/231,380, filed on Jun. 2,
2005.

Foreign Application Priority Data

(30) Dec. 7, 2004 (JP) 2004-037363
Dec. 7, 2004 (JP) 2004-037364

(51) **LOC (8) Cl.** **26-05**

(52) **U.S. Cl.** **D26/24**

(58) **Field of Classification Search** D13/180;
D6/300, 309; D7/554.2, 554.3; D9/456;
D19/1; D20/22, 27, 28, 40; D21/307, 308,
D21/349, 362, 363, 365, 374, 390; D25/109;
D26/1, 24, 72, 74, 89; 273/139, 142 R; 362/612,
362/84, 147, 362; 434/198, 214, 206; 257/79,
257/98

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

254,269 A 2/1882 Brown
2,896,951 A * 7/1959 Snow 273/148 R
3,601,401 A * 8/1971 Beck 273/244.1
4,635,351 A 1/1987 Koch et al.
5,102,129 A 4/1992 Roberts
5,458,433 A 10/1995 Stastny

5,533,636 A 7/1996 Reiker
D407,314 S * 3/1999 Rench et al. D9/456
5,912,477 A * 6/1999 Negley 257/95
D422,100 S * 3/2000 Zhang et al. D26/2
D440,227 S 4/2001 Lowenstein
D450,779 S * 11/2001 Ko D21/335
6,422,714 B1 7/2002 Hubbell
6,601,964 B2 8/2003 Wang et al.
D482,073 S * 11/2003 Nakajo et al. D20/22
D501,573 S * 2/2005 Benensohn D26/89
D516,045 S 2/2006 Street
D522,975 S 6/2006 Egawa et al.
D524,872 S * 7/2006 DiCarlo D21/343
D532,142 S * 11/2006 Matsui et al. D26/80
2006/0244879 A1 11/2006 Yoon et al.
2007/0045640 A1 * 3/2007 Erchak et al. 257/98
2007/0131954 A1 * 6/2007 Murayama et al. 257/98
2007/0133193 A1 * 6/2007 Kim 362/147

* cited by examiner

Primary Examiner—Selina Sikder

(74) *Attorney, Agent, or Firm*—Brinks Hofer Gilson & Lione

(57) **CLAIM**

I claim the ornamental design for a lighting fixture with light emitting diode, as shown and described.

DESCRIPTION

FIG. 1 is a bottom perspective view of a lighting fixture with light emitting diode of the present invention;

FIG. 2 is a right side view thereof, wherein the left side view is a mirror image thereof;

FIG. 3 is a front view thereof, wherein the rear view is a mirror image thereof;

FIG. 4 is a top view thereof; and,

FIG. 5 is a bottom view thereof.

The broken line showing of lighting fixture with light emitting diode is included for the purpose of illustrating environment and forms no part of the claimed design.

1 Claim, 2 Drawing Sheets




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5

