



US00D580286S

(12) **United States Design Patent**  
**Groszmann et al.**

(10) **Patent No.:** **US D580,286 S**  
(45) **Date of Patent:** **\*\* Nov. 11, 2008**

(54) **UNIVERSAL INSTRUMENT CALIBRATION STATION**

(75) Inventors: **Daniel Eduardo Groszmann**,  
Cambridge, MA (US); **Jonathan Schiff**,  
Andover, MA (US); **Ella Zaslavsky**,  
Marblehead, MA (US)

(73) Assignee: **General Electric Company**,  
Schenectady, NY (US)

(\*\*) Term: **14 Years**

(21) Appl. No.: **29/304,436**

(22) Filed: **Feb. 29, 2008**

**Related U.S. Application Data**

(63) Continuation-in-part of application No. 11/678,985,  
filed on Feb. 26, 2007.

(51) **LOC (8) Cl.** ..... **10-04**

(52) **U.S. Cl.** ..... **D10/78**

(58) **Field of Classification Search** ..... D10/78;  
324/67, 326, 329, 601, 658, 662, 663, 671,  
324/686, 690; 340/551, 532; 361/179-181  
See application file for complete search history.

(56) **References Cited**

**U.S. PATENT DOCUMENTS**

6,211,662 B1 \* 4/2001 Bijawat et al. .... 324/67

\* cited by examiner

*Primary Examiner*—Antoine D Davis

(74) *Attorney, Agent, or Firm*—McAndrews, Held & Malloy,  
Ltd.; Peter J. Vogel; Michael A. Dellapenna

(57) **CLAIM**

The ornamental design for a universal instrument calibration  
station, as shown and described.

**DESCRIPTION**

FIG. 1 illustrates a calibration device in accordance with an  
embodiment of the present invention.

FIG. 2 illustrates another view of a calibration device with  
receiver electronics positioned with respect to a calibration  
mount in accordance with an embodiment of the present  
invention.

FIG. 3 depicts a top perspective view of a calibration device  
having a calibration mount and receiver electronics in accor-  
dance with an embodiment of the present invention.

FIG. 4 illustrates a front perspective view of a calibration  
device with a receiver electronics holder in an open position  
in accordance with an embodiment of the present invention.

FIG. 5 depicts a side view of a calibration device with a  
receiver electronics holder in an open position in accordance  
with an embodiment of the present invention; and,

FIG. 6 depicts a side view of a calibration device with a  
receiver electronics in an undocked position in accordance  
with an embodiment of the present invention.

**1 Claim, 6 Drawing Sheets**




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5






FIG. 6

