



US00D581413S

(12) **United States Design Patent**
Kim

(10) **Patent No.:** **US D581,413 S**

(45) **Date of Patent:** **** Nov. 25, 2008**

(54) **STORAGE DEVICE WITH SLIDE**

(75) Inventor: **Hyekyung (Sophia) Kim**, Lathrop, CA (US)

(73) Assignee: **Micron Technology, Inc.**, Boise, ID (US)

(**) Term: **14 Years**

(21) Appl. No.: **29/282,603**

(22) Filed: **Jul. 25, 2007**

(51) **LOC (8) Cl.** **14-02**

(52) **U.S. Cl.** **D14/356**

(58) **Field of Classification Search** D14/411,
D14/384–385, 518, 348, 432–436, 299, 167,
D14/402, 242, 356, 358, 496, 156, 240; 455/344;
710/300–301; 361/684–686; 439/518, 139–141,
439/131, 607, 133; 365/63

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

6,456,500	B1 *	9/2002	Chen	361/752
D479,844	S *	9/2003	Slocombe et al.	D14/411
D511,519	S *	11/2005	Bone et al.	D14/432
D542,952	S *	5/2007	Bhavnani	D26/37
D544,479	S *	6/2007	Chen	D14/356
D546,328	S *	7/2007	Kobayakawa	D14/358
D547,311	S *	7/2007	Chen et al.	D14/356
D553,618	S *	10/2007	Cheng	D14/356
7,287,705	B2 *	10/2007	Tang	235/492
7,301,596	B1 *	11/2007	Morganstern et al.	349/131
D566,709	S *	4/2008	Kim	D14/356
2005/0130471	A1 *	6/2005	Regen et al.	439/131
2006/0258196	A1 *	11/2006	Chen et al.	439/141

OTHER PUBLICATIONS

Overstock.com—Cruzer [online], [retrieved on Jun. 27, 2007]. Retrieved from the Internet <URL: <http://images.overstock.com/f/102/3117/8h/www.overstock.com/images/products/11739539.jpg>>.*

* cited by examiner

Primary Examiner—Robin V. Webster

Assistant Examiner—Karen E Kearney

(74) *Attorney, Agent, or Firm*—Leffert Jay & Polglaze P.A.

(57) **CLAIM**

The ornamental design for a storage device with slide, as shown and described.

DESCRIPTION

FIG. 1 is a front isometric view of the storage device with slide in an operational configuration;

FIG. 2 is a rear view of the storage device with slide in the operational configuration;

FIG. 3 is a top view of the storage device with slide in the operational configuration, the bottom being a mirror image thereof;

FIG. 4 is a front view of the storage device with slide in the operational configuration;

FIG. 5 is a left-side view of the storage device with slide in the operational configuration;

FIG. 6 is a right-side view of the storage device with slide in the operational configuration;

FIG. 7 is a front isometric view of the storage device with slide in a non-operational configuration;

FIG. 8 is a rear view of the storage device with slide in the non-operational configuration;

FIG. 9 is a top view of the storage device with slide in the non-operational configuration, the bottom being a mirror image thereof;



FIG. 10 is a front view of the storage device with slide in the non-operational configuration;

FIG. 11 is a left-side view of the storage device with slide in the non-operational configuration; and,

FIG. 12 is a right-side view of the storage device with slide in the non-operational configuration.

The broken-line showing of a Universal Serial Bus (USB) male connector in the various figures is for environmental purposes only and forms no part of the claimed design.

1 Claim, 3 Drawing Sheets






FIG. 1




FIG. 7

FIG. 2




FIG. 3





FIG. 4




FIG. 5




FIG. 6

FIG. 8




FIG. 9





FIG. 10




FIG. 11




FIG. 12