

US00D582806S

(12) United States Design Patent

Schmid-Schweiger

(10) Patent No.:

US D582,806 S

(45) **Date of Patent:**

** Dec. 16, 2008

(54) GPS RECEIVER

(75) In	ventor: M	arie Schn	nid-Schweig	ger, Munich	(DE)
---------	------------------	-----------	-------------	-------------	------

(73) Assignee: Jentro Technologies GmbH, Munich

(DE)

(**) Term: **14 Years**

(21) Appl. No.: 29/265,554

(22) Filed: Sep. 5, 2006

(30)

Foreign Application Priority Data

Jun. 3, 2006	(EM)	
Jun. 3, 2006		
Jun. 3, 2006	(EM)	

(51) LOC (8) Cl.	10-04
(52) U.S. Cl.	D10/65
(58) Field of Classification Search	D10/65,
D10/78; D14/347; 342/351, 419, 457, 35	/
343/702; 345/87, 104, 133, 1	
345/901–905; 348/180, 184, 315, 73	,
364/499; 701/206–2	209, 213, 214

See application file for complete search history.

(56) References Cited

U.S. PATENT DOCUMENTS

D331,201 S	* 11/1992	Koch D10/65
D364,850 S	* 12/1995	Estrada et al D10/65
5,546,092 A	* 8/1996	Kurokawa et al 342/357.06
6,199,012 B1	* 3/2001	Hasegawa 701/208
6,674,411 B2	* 1/2004	Boyle 343/860
6,952,602 B2	* 10/2005	Deng 343/702
D524,665 S	* 7/2006	Taisto

^{*} cited by examiner

Primary Examiner—Antoine D Davis


(74) Attorney, Agent, or Firm—Stites & Harbison PLLC; Douglas E. Jackson

(57) CLAIM

The ornamental design for a GPS receiver, as shown and described.

DESCRIPTION

- FIG. 1 is a perspective front, bottom and right side view of a first embodiment of a GPS receiver according to the present invention.
- FIG. 2 is front view of the first embodiment of the GPS receiver depicted in FIG. 1.
- FIG. 3 is rear view of the first embodiment of the GPS receiver depicted in FIG. 1.
- FIG. 4 is a right side view of the first embodiment of the GPS receiver depicted in FIG. 1.
- FIG. 5 is a left side view of the first embodiment of the GPS receiver depicted in FIG. 1.
- FIG. 6 is a top view of the first embodiment of the GPS receiver depicted in FIG. 1.
- FIG. 7 is a bottom view of the first embodiment of the GPS receiver depicted in FIG. 1.
- FIG. 8 is a perspective front, bottom and right side view of a second embodiment of a GPS receiver according to the present invention.
- FIG. 9 is front view of the second embodiment of the GPS receiver depicted in FIG. 8.
- FIG. 10 is rear view of the second embodiment of the GPS receiver depicted in FIG. 8.
- FIG. 11 is a right side view of the second embodiment of the GPS receiver depicted in FIG. 8.
- FIG. 12 is a left side view of the second embodiment of the GPS receiver depicted in FIG. 8.
- FIG. 13 is a top view of the second embodiment of the GPS receiver depicted in FIG. 8.
- FIG. 14 is a bottom view of the second embodiment of the GPS receiver depicted in FIG. 8.




- FIG. 15 is a perspective front, bottom and right side view of a third embodiment of a GPS receiver according to the present invention.
- FIG. 16 is front view of the third embodiment of the GPS receiver depicted in FIG. 15.
- FIG. 17 is rear view of the third embodiment of the GPS receiver depicted in FIG. 15.
- FIG. 18 is a right side view of the third embodiment of the GPS receiver depicted in FIG. 15.
- FIG. 19 is a left side view of the third embodiment of the GPS receiver depicted in FIG. 15.
- FIG. 20 is a top view of the third embodiment of the GPS receiver depicted in FIG. 15.
- FIG. 21 is a bottom view of the third embodiment of the GPS receiver depicted in FIG. 15.
- FIG. 22 is a perspective front, bottom and right side view of a fourth embodiment of a GPS receiver according to the present invention.
- FIG. 23 is front view of the fourth embodiment of the GPS receiver depicted in FIG. 22.
- FIG. 24 is rear view of the fourth embodiment of the GPS receiver depicted in FIG. 22.
- FIG. 25 is a right side view of the fourth embodiment of the GPS receiver depicted in FIG. 22.
- FIG. 26 is a left side view of the fourth embodiment of the GPS receiver depicted in FIG. 22.
- FIG. 27 is a top view of the fourth embodiment of the GPS receiver depicted in FIG. 22.
- FIG. 28 is a bottom view of the fourth embodiment of the GPS receiver depicted in FIG. 22.
- FIG. **29** is a perspective front, bottom and right side view of a fifth embodiment of a GPS receiver according to the present invention.
- FIG. 30 is front view of the fifth embodiment of the GPS receiver depicted in FIG. 29.
- FIG. 31 is rear view of the fifth embodiment of the GPS receiver depicted in FIG. 29.
- FIG. 32 is a right side view of the fifth embodiment of the GPS receiver depicted in FIG. 29.
- FIG. 33 is a left side view of the fifth embodiment of the GPS receiver depicted in FIG. 29.
- FIG. 34 is a top view of the fifth embodiment of the GPS receiver depicted in FIG. 29.
- FIG. 35 is a bottom view of the fifth embodiment of the GPS receiver depicted in FIG. 29.
- FIG. 36 is a perspective front, bottom and right side view of a sixth embodiment of a GPS receiver according to the present invention.
- FIG. 37 is front view of the sixth embodiment of the GPS receiver depicted in FIG. 36.
- FIG. 38 is rear view of the sixth embodiment of the GPS receiver depicted in FIG. 36.
- FIG. 39 is a right side view of the sixth embodiment of the GPS receiver depicted in FIG. 36.
- FIG. 40 is a left side view of the sixth embodiment of the GPS receiver depicted in FIG. 36.
- FIG. 41 is a top view of the sixth embodiment of the GPS receiver depicted in FIG. 36.


- FIG. 42 is a bottom view of the sixth embodiment of the GPS receiver depicted in FIG. 36.
- FIG. 43 is a perspective front, bottom and right side view of a seventh embodiment of a GPS receiver according to the present invention.
- FIG. 44 is front view of the seventh embodiment of the GPS receiver depicted in FIG. 43.
- FIG. 45 is rear view of the seventh embodiment of the GPS receiver depicted in FIG. 43.
- FIG. **46** is a right side view of the seventh embodiment of the GPS receiver depicted in FIG. **43**.
- FIG. 47 is a left side view of the seventh embodiment of the GPS receiver depicted in FIG. 43.
- FIG. 48 is a top view of the seventh embodiment of the GPS receiver depicted in FIG. 43.
- FIG. **49** is a bottom view of the seventh embodiment of the GPS receiver depicted in FIG. **43**.
- FIG. **50** is a perspective front, bottom and right side view of a eighth embodiment of a GPS receiver according to the present invention.
- FIG. **51** is front view of the eighth embodiment of the GPS receiver depicted in FIG. **50**.
- FIG. **52** is rear view of the eighth embodiment of the GPS receiver depicted in FIG. **50**.
- FIG. **53** is a right side view of the eighth embodiment of the GPS receiver depicted in FIG. **50**.
- FIG. **54** is a left side view of the eighth embodiment of the GPS receiver depicted in FIG. **50**.
- FIG. **55** is a top view of the eighth embodiment of the GPS receiver depicted in FIG. **50**.
- FIG. **56** is a bottom view of the eighth embodiment of the GPS receiver depicted in FIG. **50**.
- FIG. 57 is a perspective front, bottom and right side view of a ninth embodiment of a GPS receiver according to the present invention.
- FIG. **58** is front view of the ninth embodiment of the GPS receiver depicted in FIG. **57**.
- FIG. **59** is rear view of the ninth embodiment of the GPS receiver depicted in FIG. **57**.
- FIG. **60** is a right side view of the ninth embodiment of the GPS receiver depicted in FIG. **57**.
- FIG. **61** is a left side view of the ninth embodiment of the GPS receiver depicted in FIG. **57**.
- FIG. **62** is a top view of the ninth embodiment of the GPS receiver depicted in FIG. **57**.
- FIG. **63** is a bottom view of the ninth embodiment of the GPS receiver depicted in FIG. **57**.
- FIG. **64** is a perspective front, bottom and right side view of a tenth embodiment of a GPS receiver according to the present invention.
- FIG. 65 is front view of the tenth embodiment of the GPS receiver depicted in FIG. 64.
- FIG. **66** is rear view of the tenth embodiment of the GPS receiver depicted in FIG. **64**.
- FIG. 67 is a right side view of the tenth embodiment of the GPS receiver depicted in FIG. 64.
- FIG. **68** is a left side view of the tenth embodiment of the GPS receiver depicted in FIG. **64**.


- FIG. **69** is a top view of the tenth embodiment of the GPS receiver depicted in FIG. **64**.
- FIG. 70 is a bottom view of the tenth embodiment of the GPS receiver depicted in FIG. 64.
- FIG. 71 is a perspective front, bottom and right side view of a eleventh embodiment of a GPS receiver according to the present invention.
- FIG. 72 is front view of the eleventh embodiment of the GPS receiver depicted in FIG. 71.
- FIG. 73 is rear view of the eleventh embodiment of the GPS receiver depicted in FIG. 71.
- FIG. 74 is a right side view of the eleventh embodiment of the GPS receiver depicted in FIG. 71.
- FIG. 75 is a left side view of the eleventh embodiment of the GPS receiver depicted in FIG. 71.
- FIG. **76** is a top view of the eleventh embodiment of the GPS receiver depicted in FIG. **71**.
- FIG. 77 is a bottom view of the eleventh embodiment of the GPS receiver depicted in FIG. 71.
- FIG. 78 is a perspective front, bottom and right side view of a twelfth embodiment of a GPS receiver according to the present invention.
- FIG. 79 is front view of the twelfth embodiment of the GPS receiver depicted in FIG. 78.
- FIG. **80** is rear view of the twelfth embodiment of the GPS receiver depicted in FIG. **78**.
- FIG. **81** is a right side view of the twelfth embodiment of the GPS receiver depicted in FIG. **78**.
- FIG. 82 is a left side view of the twelfth embodiment of the GPS receiver depicted in FIG. 78.
- FIG. 83 is a top view of the twelfth embodiment of the GPS receiver depicted in FIG. 78.


- FIG. **84** is a bottom view of the twelfth embodiment of the GPS receiver depicted in FIG. **78**.
- FIG. **85** is a perspective front, bottom and right side view of a thirteenth embodiment of a GPS receiver according to the present invention.
- FIG. **86** is front view of the thirteenth embodiment of the GPS receiver depicted in FIG. **85**.
- FIG. 87 is rear view of the thirteenth embodiment of the GPS receiver depicted in FIG. 85.
- FIG. **88** is a right side view of the thirteenth embodiment of the GPS receiver depicted in FIG. **85**.
- FIG. **89** is a left side view of the thirteenth embodiment of the GPS receiver depicted in FIG. **85**.
- FIG. 90 is a top view of the thirteenth embodiment of the GPS receiver depicted in FIG. 85.
- FIG. **91** is a bottom view of the thirteenth embodiment of the GPS receiver depicted in FIG. **85**.
- FIG. 92 is a perspective front, bottom and right side view of a fourteenth embodiment of a GPS receiver according to the present invention.
- FIG. 93 is front view of the fourteenth embodiment of the GPS receiver depicted in FIG. 92.
- FIG. 94 is rear view of the fourteenth embodiment of the GPS receiver depicted in FIG. 92.
- FIG. 95 is a right side view of the fourteenth embodiment of the GPS receiver depicted in FIG. 92.
- FIG. 96 is a left side view of the fourteenth embodiment of the GPS receiver depicted in FIG. 92.
- FIG. 97 is a top view of the fourteenth embodiment of the GPS receiver depicted in FIG. 92; and,
- FIG. 98 is a bottom view of the fourteenth embodiment of the GPS receiver depicted in FIG. 92.

1 Claim, 84 Drawing Sheets























<u>5</u>





























4













































Q V





 α





1



































































































































U.S. Patent

Dec. 16, 2008

