



US00D583779S

(12) **United States Design Patent**
Kuriyama et al.

(10) **Patent No.:** **US D583,779 S**

(45) **Date of Patent:** **** Dec. 30, 2008**

(54) **ELECTROLYTIC PLATING ANODE**

(75) Inventors: **Fumio Kuriyama**, Tokyo (JP); **Masaaki Kimura**, Tokyo (JP)

(73) Assignee: **Ebara Corporation**, Tokyo (JP)

(**) Term: **14 Years**

(21) Appl. No.: **29/262,881**

(22) Filed: **Jul. 13, 2006**

(51) **LOC (8) Cl.** **13-03**

(52) **U.S. Cl.** **D13/182**

(58) **Field of Classification Search** D13/182;
D26/1, 24, 72, 74, 89; 204/280, 286.1, 297.01,
204/297.1; 205/98, 528; 206/454, 711; 361/523,
361/528, 529; 257/678

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

4,203,127	A *	5/1980	Tegge, Jr.	206/710
5,429,733	A *	7/1995	Ishida	204/224 R
5,537,042	A *	7/1996	Beutler et al.	324/432
5,657,198	A *	8/1997	Flener	361/220
5,869,196	A *	2/1999	Wong et al.	428/613
D411,516	S *	6/1999	Imafuku et al.	D13/182
6,071,388	A *	6/2000	Uzoh	204/287
6,248,222	B1 *	6/2001	Wang	204/297.09
6,251,238	B1 *	6/2001	Kaufman et al.	204/242
6,309,523	B1 *	10/2001	Prasnikar et al.	204/278.5
6,365,020	B1	4/2002	Yoshioka et al.	
6,383,352	B1 *	5/2002	Shyu et al.	204/292
6,471,847	B2 *	10/2002	Talieh et al.	205/147
6,613,200	B2 *	9/2003	Li et al.	204/198
6,716,332	B1	4/2004	Yoshioka et al.	
7,223,323	B2 *	5/2007	Yang et al.	204/242
2002/0112953	A1 *	8/2002	Kohut	204/280

2003/0221956	A1 *	12/2003	Herchen et al.	204/280
2004/0231978	A1 *	11/2004	White	204/280
2005/0029641	A1 *	2/2005	Ikeda	257/678
2006/0124454	A1 *	6/2006	Wurm et al.	204/286.1
2008/0017505	A1 *	1/2008	Kuriyama et al.	204/286.1

* cited by examiner

Primary Examiner—Selina Sikder

(74) *Attorney, Agent, or Firm*—Wenderoth, Lind & Ponack, L.L.P.

(57) **CLAIM**

The ornamental design for an electrolytic plating anode, as shown and described.

DESCRIPTION

The claimed electrolytic plating anode is used to perform an electrolytic plating process in a plating bath when a voltage is applied via an anode shaft connected to the electrolytic plating anode.

FIG. 1 is a front elevation view of an electrolytic plating anode;

FIG. 2 is a rear view of the electrolytic plating anode shown in FIG. 1;

FIG. 3 is a top plan view of the electrolytic plating anode shown in FIG. 1, wherein the broken lines form no part of the claimed design;

FIG. 4 is a bottom plan view of the electrolytic plating anode shown in FIG. 1;

FIG. 5 is a right side view of the electrolytic plating anode shown in FIG. 1; and,

FIG. 6 is a left side view of the electrolytic plating anode shown in FIG. 1.

1 Claim, 6 Drawing Sheets




FIG. 1




FIG. 2




FIG. 3



FIG. 4



FIG. 5




FIG. 6

