



US00D586403S

(12) **United States Design Patent**
Chambers et al.

(10) **Patent No.:** **US D586,403 S**

(45) **Date of Patent:** **** Feb. 10, 2009**

(54) **DEVICE FOR SECURING A BALLOON TO A CORRUGATED SIGN**

D449,222 S * 10/2001 Young et al. D8/382
6,688,939 B1 * 2/2004 Novak 446/220

(76) Inventors: **Andrew C. Chambers**, 11032
Merganser Ter., Chesterfield, VA (US)
23838; **Geoffrey H. Richardson**, 11011
Merganser Ter., Chesterfield, VA (US)
23838

* cited by examiner

Primary Examiner—Caron Veynar
Assistant Examiner—Mary Ann Calabrese
(74) *Attorney, Agent, or Firm*—Norman B. Rainer

(**) Term: **14 Years**

(57) **CLAIM**

(21) Appl. No.: **29/287,082**

The ornamental design for a device for securing a balloon to a corrugated sign, as shown and described.

(22) Filed: **Jun. 25, 2007**

DESCRIPTION

(51) **LOC (9) Cl.** **20-03**

FIG. 1 is a front perspective view of a device for securing a balloon to a corrugated sign, showing a first embodiment of our new design having circular ridges;

(52) **U.S. Cl.** **D20/43**

FIG. 2 is a front view thereof, the opposite side being identical thereto;

(58) **Field of Classification Search** D20/10,
D20/19, 41-43, 99; 40/584, 607.11, 607.13,
40/607.14, 620, 642.02, 661, 658, 666, 668;
D8/349, 367, 382; 24/442, 572.1; 52/309.1;
84/442.4; 206/338, 340; 211/13.1, 113;
248/210; 256/48; 269/45; 411/17, 384,
411/400, 421, 455, 485; 446/220

FIG. 3 is a side view thereof, the opposite side being identical thereto;

See application file for complete search history.

FIG. 4 is a top view thereof, showing said device in use, inserted into a channel of a corrugated sign shown in fragmentary broken lines forming no part of the claimed design;

FIG. 5 is a bottom view of the device of FIG. 1;

(56) **References Cited**

U.S. PATENT DOCUMENTS

240,083	A *	4/1881	Hovel-Thurlow-Cumming-Bruce	256/48
318,566	A *	5/1885	Jones	411/455
546,269	A *	9/1895	Countant	411/455
2,028,528	A *	1/1936	Sipe	411/455
2,867,807	A *	1/1959	Anstett	206/340
3,921,496	A *	11/1975	Hedlerman	411/17
4,219,980	A *	9/1980	Loyd	52/309.1
4,718,802	A *	1/1988	Rockenfeller et al.	411/421
4,939,972	A *	7/1990	Falberg	84/422.4
4,943,039	A *	7/1990	Jackson	269/45
4,953,713	A *	9/1990	Yaffe	211/13.1
D346,954	S *	5/1994	Vandermast	D8/382
5,788,198	A *	8/1998	Sharpe	248/210
5,823,365	A *	10/1998	Page	211/113

FIG. 6 is a perspective front view of said device in reduced size shown in use inserted into a channel of a corrugated sign and securing a tethered balloon thereto. The said sign, tether and balloon being represented in broken line and not part of the claimed design;

FIG. 7 is a front perspective view of a second embodiment of the said device showing our new design;

FIG. 8 is a front view thereof, the opposite side being identical thereto;

FIG. 9 is a side view thereof, the opposite side being identical thereto; and,

FIG. 10 is a bottom view thereof.

1 Claim, 3 Drawing Sheets






FIG. 3




FIG. 2




FIG. 1




FIG. 4



FIG. 5




FIG. 6




FIG. 7




FIG. 8



FIG. 9



FIG. 10