



US00D587493S

(12) **United States Design Patent**  
**Skidis**

(10) **Patent No.:** **US D587,493 S**

(45) **Date of Patent:** **\*\* Mar. 3, 2009**

(54) **JEWELRY STORAGE DEVICE**

(76) **Inventor:** **Darlene J. Skidis**, 1402 Villas Estates  
Dr., St. Louis, MO (US) 63026

(\*\*) **Term:** **14 Years**

(21) **Appl. No.:** **29/301,151**

(22) **Filed:** **Feb. 14, 2008**

(51) **LOC (9) Cl.** ..... **06-04**

(52) **U.S. Cl.** ..... **D6/467**

(58) **Field of Classification Search** ..... D6/315,  
D6/514, 513, 434, 470-475, 467, 466, 449,  
D6/454, 567, 450, 630, 566, 571, 553; 248/444.1,  
248/445, 107; 211/13.1, 85.2, 85.26, 106.1;  
206/6.1; 312/204, 140.4, 116, 137, 114  
See application file for complete search history.

(56) **References Cited**

**U.S. PATENT DOCUMENTS**

3,081,881	A *	3/1963	Seeger	.....	211/85.3
3,276,601	A *	10/1966	Haggerty	.....	211/119
4,136,784	A *	1/1979	Knobel et al.	.....	211/119
4,401,219	A *	8/1983	Mink	.....	206/566
4,966,287	A *	10/1990	Snyder	.....	211/85.2
D313,906	S *	1/1991	Lublin	.....	D6/467
D321,790	S *	11/1991	Martorella	.....	D3/278
5,209,344	A *	5/1993	Smith	.....	206/6.1
5,240,120	A *	8/1993	McDonough	.....	211/85.2
5,295,587	A *	3/1994	Downes et al.	.....	211/85.2
D350,027	S *	8/1994	Downes et al.	.....	D3/278
5,427,230	A *	6/1995	Mattox	.....	206/6.1
D364,519	S *	11/1995	Daughtry	.....	D6/513
D369,261	S *	4/1996	Brink	.....	D6/514
D387,929	S *	12/1997	Stewart	.....	D6/513
6,371,285	B1 *	4/2002	DuBois	.....	206/6.1

6,450,595	B1 *	9/2002	Simon et al.	.....	312/204
6,769,555	B2 *	8/2004	Brady	.....	211/85.3
7,059,469	B2 *	6/2006	Simon et al.	.....	206/6.1
D543,367	S *	5/2007	Sack	.....	D6/315
D549,502	S *	8/2007	DeLatte	.....	D6/514
D582,186	S *	12/2008	Smith	.....	D6/513

\* cited by examiner

*Primary Examiner*—Caron Veynar

*Assistant Examiner*—Sydney R Buffalow

(74) *Attorney, Agent, or Firm*—Kevin L. Klug

(57) **CLAIM**

The ornamental design for a jewelry storage device, as shown and described.

**DESCRIPTION**

FIG. 1 is a front plan view of a jewelry storage device in an open position;

FIG. 2 is a rear plan view thereof;

FIG. 3 is a left side plan view thereof;

FIG. 4 is a right side plan view thereof;

FIG. 5 is a top side plan view thereof;

FIG. 6 is a bottom side plan view thereof;

FIG. 7 is a front plan view of a jewelry storage device in a closed position;

FIG. 8 is a rear plan view thereof;


FIG. 9 is a left side plan view thereof;

FIG. 10 is a right side plan view thereof;

FIG. 11 is a top side plan view thereof; and,

FIG. 12 is a bottom side plan view thereof.

**1 Claim, 7 Drawing Sheets**






Fig. 1




Fig. 2



Fig. 4



Fig. 3



Fig. 5



Fig. 6




Fig. 8




Fig. 7




Fig. 10




Fig. 9




Fig. 11



Fig. 12