

US00D588975S

(12) United States Design Patent Spater et al.

(45) **Date of Patent:**

(10) Patent No.:

US D588,975 S ** Mar. 24, 2009

(54) TIRE COVER

(75) Inventors: Christopher B. Spater, Portsmouth, NH

(US); Ryan C. Meers, Redland Bead,

CA (US)

(73) Assignee: Motivation Design, LLC, Salisbury,

MA (US)

(**) Term: **14 Years**

(21) Appl. No.: 29/299,994

(22) Filed: Jan. 8, 2008

See application file for complete search history.

(56) References Cited

U.S. PATENT DOCUMENTS

799,662 A 9/1905 Nathan

(Continued)

FOREIGN PATENT DOCUMENTS

DE	203 03 322 U1	6/2003
GB	M07513 A	12/1912
GB	2106841 A	4/1983
WO	WO 97/11011	3/1997

OTHER PUBLICATIONS

Wheel Butler [online], Retrieved from the Internet on May 2, 2005 URL:http://www.preyss.com/html/portfolio.html.

Primary Examiner—Stacia Cadmus (74) Attorney, Agent, or Firm—Antoinette G Giugliano PC

(57) CLAIM

The ornamental design for a tire cover, as shown and described.

DESCRIPTION

The tire cover of the present invention is designed to allow a user to change, transport or store tires without getting dirty.

FIG. 1 is a perspective view of the tire cover of the present invention, shaped as if the cover was on a tire.

FIG. 2 is a front view thereof.

FIG. 3 is back view thereof.

FIG. 4 is a top view thereof.

FIG. 5 is a bottom view thereof.


FIG. 6 is a side view thereof.

FIG. 7 is another side view thereof; and,

FIG. 8 is a perspective view of the tire cover of the present invention, shaped as if the cover was not on a tire.

The tire cover of the present invention has features for clean tire changing and transport. Those features include flexible, liquid resistant material that essentially covers the side walls of the tire as well as the tire tread. Additionally, the tire cover is shaped so that when it is fitted on the tire, an opening exists and allows for the user to access inner portions of the tire, e.g., lug nuts. Hence, the opening allows for a user to change a tire while the tire is covered. Additionally, the tire cover has handles that allow a covered tire to be carried and transported. The tire cover further includes hook and loop fasteners to adjust the circumference of the tire cover to fit several size tires.

1 Claim, 6 Drawing Sheets



^{*} cited by examiner

US D588,975 S Page 2

U.S. PATENT	DOCUMENTS	5,513,788 A 5,547,187 A		Cochrane et al. Spykerman
1,689,438 A 10/1928	Jellison et al.	2,805,882 A		1.7
1,718,969 A * 7/1929	Lockwood 206/304	5,803,324 A		
1,755,133 A * 4/1930	Rowe 206/304.1	, ,	10/1998	
1,947,145 A 2/1934	Zerk	5,951,232 A		
2,348,084 A * 5/1944	MacChesney et al 206/304	5,992,942 A		
2,639,934 A 5/1953	Swinamer	D418,792 S *	1/2000	Iampen D12/202
2,676,831 A 4/1954	Scuderi	6,033,003 A	3/2000	Bell et al.
D179,516 S * 1/1957	Kammeyer D12/202	6,044,968 A	4/2000	Iampen
2,849,045 A * 8/1958	Anderson 206/304.1	6,116,415 A	9/2000	Rastelli
D217,412 S * 4/1970	Moquin D12/202	6,142,192 A	11/2000	Dickinson et al.
3,712,586 A 1/1973	Nicholson	6,155,323 A	12/2000	Gougelet
4,106,681 A 8/1978	Bott	6,189,749 B1	2/2001	Sato et al.
4,126,169 A 11/1978	Magnuson et al.	6,273,159 B1	8/2001	Page
4,230,246 A 10/1980	Wilson	6,425,639 B1	7/2002	Getzelman
4,294,405 A 10/1981	Ross	6,428,112 B1	8/2002	Passoth et al.
5,076,477 A 12/1991	Colgan	6,439,281 B1	8/2002	Hogg
5,228,608 A 7/1993	Stout, III	6,457,780 B1	10/2002	Ernst
5,439,727 A * 8/1995	Riggs et al 150/154	6,499,591 B1	12/2002	Rizzo et al.




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7



FIG. 8