



US00D589880S

(12) **United States Design Patent**
Steigleman, Jr. et al.

(10) **Patent No.:** **US D589,880 S**
(45) **Date of Patent:** **** Apr. 7, 2009**

(54) **TRANSPARENT CERAMIC INSULATOR FOR SPARKPLUGS**

(76) Inventors: **Robert Lee Steigleman, Jr.**, 631 Chaparral, Mira Loma, CA (US) 91752;
Jimmy Robert Allen, II, 3436 Briarvale St., Corona, CA (US) 92879

(**) Term: **14 Years**

(21) Appl. No.: **29/240,039**

(22) Filed: **Oct. 8, 2005**

(51) **LOC (9) Cl.** **13-03**

(52) **U.S. Cl.** **D13/131; D13/127**

(58) **Field of Classification Search** D13/118,
D13/127-129, 156, 131, 154; 174/35, 66,
174/188, 138, 176, 35 GC, 138 F
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

D55,133 S *	5/1920	Kumler et al.	D13/127
2,447,157 A *	8/1948	Burrell et al.	439/127
2,499,823 A *	3/1950	Gogel	174/152 S
2,665,673 A *	1/1954	Woofter	439/125
3,193,615 A *	7/1965	Burrows	174/138 F
3,313,972 A *	4/1967	Beesch	313/130
D209,397 S *	11/1967	Weiner	D13/127
3,528,051 A *	9/1970	Cooper et al.	439/447
3,639,681 A *	2/1972	Ettlinger	174/138 F
3,783,489 A *	1/1974	Duffner	29/281.5
D235,651 S *	7/1975	Jukes	D13/127
4,091,350 A *	5/1978	Buffington, Jr.	336/208
D274,425 S *	6/1984	Labutski, III	D13/127
4,563,158 A *	1/1986	Meyer	445/7
D319,626 S *	9/1991	Murakami	D13/156
D326,843 S *	6/1992	Sklar	D13/129
D340,440 S *	10/1993	Fuller et al.	D13/127
D349,683 S *	8/1994	Arens	D13/127

D391,226 S *	2/1998	Coombs et al.	D13/127
D407,067 S *	3/1999	Ekerson	D13/127
6,130,498 A *	10/2000	Shimizu et al.	313/141
D459,697 S *	7/2002	Schaus	D13/127
6,566,792 B2 *	5/2003	Nishikawa	313/118
D494,136 S *	8/2004	Vesecky	D13/127
7,049,734 B2 *	5/2006	Tamura	313/143
2005/0194878 A1 *	9/2005	Watanabe	313/141

* cited by examiner

Primary Examiner—Daniel D Bui

Assistant Examiner—Thomas J Johannes

(57) **CLAIM**

The ornamental design for a transparent ceramic insulator for sparkplugs, as shown and described.

DESCRIPTION

FIG. 1 is an elevated perspective view of a transparent ceramic insulator for sparkplugs according to our new design.

FIG. 2 is a front view thereof.

FIG. 3 is a rear view thereof.

FIG. 4 is a right side view thereof.

FIG. 5 is a left side view thereof.

FIG. 6 is a top view thereof, shown enlarged for clarity; and,


FIG. 7 is a bottom view thereof, shown enlarged for clarity.

The broken lines showing, the electrode, the shell, and the terminal of the sparkplug, in the figure drawings are included for illustrative purposes only and form no part of the claimed design.

The special dot-dash line in FIG. 6 defines the bounds of the claimed design and forms no part of the claimed design.

The transparency of the insulator is a unique characteristic in the field of sparkplugs and is intended for its visual effect only.

1 Claim, 7 Drawing Sheets






FIG 1




FIG 2




FIG 3




FIG 4




FIG 5




FIG 6




FIG 7