



US00D591005S

(12) **United States Design Patent**
Bennett

(10) **Patent No.:** **US D591,005 S**
(45) **Date of Patent:** **** Apr. 21, 2009**

(54) **ANIMAL SAFETY SEAT**

(76) **Inventor:** **Gary Ray Bennett**, 6945 Wake Hurst Pl., Cumming, GA (US) 30040

(**) **Term:** **14 Years**

(21) **Appl. No.:** **29/304,929**

(22) **Filed:** **Mar. 10, 2008**

(51) **LOC (9) Cl.** **30-06**

(52) **U.S. Cl.** **D30/118**

(58) **Field of Classification Search** D30/118;
D6/334–335, 349, 359, 361, 377, 382, 388,
D6/595–597, 601, 604; D21/520–521; 5/417;
119/28.5, 706

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

| | | | | | | |
|-----------|----|---|---------|---------------|-------|-----------|
| D215,543 | S | * | 10/1969 | Poor et al. | | D6/604 |
| D220,953 | S | * | 6/1971 | Des Pres | | D6/361 |
| D245,716 | S | * | 9/1977 | Russo | | D30/118 |
| 4,103,810 | A | * | 8/1978 | Hickey | | D30/118 |
| D281,553 | S | * | 12/1985 | Glawe | | D6/333 |
| D300,694 | S | * | 4/1989 | Krok | | D6/333 |
| D309,514 | S | * | 7/1990 | Marcus et al. | | D30/118 |
| 5,123,377 | A | * | 6/1992 | Edwards | | 119/28.5 |
| 5,147,109 | A | * | 9/1992 | Jolly | | 297/217.4 |
| D334,848 | S | * | 4/1993 | Mariol | | D6/333 |
| D347,120 | S | * | 5/1994 | Artz | | D6/333 |
| D351,506 | S | * | 10/1994 | Artz | | D6/333 |
| D376,447 | S | * | 12/1996 | Stump | | D30/118 |
| D443,686 | S | * | 6/2001 | Gonzalez | | D6/595 |
| 6,588,365 | B2 | * | 7/2003 | Best Wright | | 119/28.5 |
| 7,383,789 | B2 | * | 6/2008 | Wilkes | | 119/28.5 |

| | | | | | | |
|--------------|----|---|---------|-------------|-------|----------|
| 7,448,345 | B1 | * | 11/2008 | O'Donnell | | 119/28.5 |
| 2001/0042516 | A1 | * | 11/2001 | Best Wright | | 119/28.5 |
| 2007/0084411 | A1 | * | 4/2007 | Bennett | | 119/28.5 |
| 2008/0257269 | A1 | * | 10/2008 | Kline | | 119/28.5 |

* cited by examiner

Primary Examiner—Cathy Anne MacCormac
(74) *Attorney, Agent, or Firm*—Carlton Fields

(57) **CLAIM**

The ornamental design for a animal safety seat, as shown and described.

DESCRIPTION

FIG. 1 is a perspective view of a animal safety seat, illustrated in an open position, showing my new design;

FIG. 2 is a perspective view of a animal safety seat, illustrated in closed position, showing my new design;

FIG. 3 is a front elevational view of FIG. 2;

FIG. 4 is a rear elevational view of the invention, illustrated in the open position;



FIG. 5 is a left-side elevational view of the invention, illustrated in the open position, the right-side elevational view being a mirror image thereof;

FIG. 6 is a top plan view of the invention, illustrated in the open position; and,

FIG. 7 is a bottom plan view of the invention, illustrated in the open position.

The broken lines showing a dog in FIG. 1 are included for the purpose of illustrating the invention in use, and form no part of the claimed design.

1 Claim, 3 Drawing Sheets






FIG. 2




FIG. 1




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7