



US00D593103S

(12) **United States Design Patent**
Richter

(10) **Patent No.:** **US D593,103 S**
(45) **Date of Patent:** **** May 26, 2009**

(54) **APPARATUS SUPPORT DEVICE HOLDER**

(76) Inventor: **Harald Richter**, Höhenstrasse 32, 76331
Engelbrand (DE)

(**) Term: **14 Years**

(21) Appl. No.: **29/293,884**

(22) Filed: **Dec. 17, 2007**

(51) **LOC (9) Cl.** **08-07**

(52) **U.S. Cl.** **D14/447; D14/253**

(58) **Field of Classification Search** D14/447,
D14/451, 452, 328, 336, 356, 371, 374, 375,
D14/376, 432, 434, 439, 448, 454, 457, 239,
D14/251, 252, 341, 224, 253, 316, 129, 209,
D14/217, 237, 238, 458, 459, 460, 461; D10/65;
D6/444, 513, 396, 419, 420, 473, 474, 512;
D8/349, 355, 363, 373, 380, 354; D19/92,
D19/95; D23/370, 387; 248/176.1, 220.21,
248/223.31, 274.1, 276.1, 281.11, 284.1,
248/286.1, 309.1, 316.1, 323, 324, 346.3,
248/349.1, 371, 398, 917, 918, 919, 920,
248/921, 922, 923, 205.5, 121, 124.1, 127,
248/177.1, 201, 205.1, 291.1, 313, 346.01,
248/346.03, 415; D12/415; 312/223.3; 348/825,
348/836; 379/446, 454; 361/681, 683, 687,
361/695

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

D487,270 S * 3/2004 Richter D14/447
D521,850 S * 5/2006 Richter et al. D8/354
D530,333 S * 10/2006 Richter D14/447
D533,174 S * 12/2006 Richter D14/251
D545,825 S * 7/2007 Richter D14/447
D545,826 S * 7/2007 Richter D14/447
D553,957 S * 10/2007 Brassard D8/363
D553,958 S * 10/2007 Brassard D8/363
D553,959 S * 10/2007 Brassard D8/363
D554,136 S * 10/2007 Richter D14/447
D554,137 S * 10/2007 Richter D14/447
D566,530 S * 4/2008 Brassard D8/363

2004/0256529 A1 * 12/2004 Richter 248/309.1
2007/0080267 A1 * 4/2007 Richter 248/160

* cited by examiner

Primary Examiner—Jennifer Rivard

Assistant Examiner—Angela J Lee

(74) *Attorney, Agent, or Firm*—Klaus J. Bach

(57) **CLAIM**

The ornamental design for an apparatus support device holder, as shown and described.

DESCRIPTION

FIG. 1 is a front view of an apparatus support device holder, FIG. 2 is a rear view of an apparatus support device holder shown in FIG. 1,

FIG. 3 is a right side view of the apparatus support device holder shown in FIG. 1,

FIG. 4 is a left side view of the apparatus support device holder shown in FIG. 1,

FIG. 5 is a right side perspective view of the apparatus support device holder shown in FIG. 1,


FIG. 6 is a left side perspective view of the apparatus support device holder shown in FIG. 1; and,

FIG. 7 is a bottom view of the apparatus support device holder shown in FIG. 1.

The four small protrusions shown on the surface of the locking lever in FIGS. 3 and 4 are ribs extending over the full width of the locking lever. They should be shown in broken lines as they form no part of the claimed design. But, because of their small size, the broken lines can not be shown and therefore are described in this statement for clarity.

The apparatus support device holder is used for supporting an apparatus support device specifically adapted to cradling a particular apparatus such as a wireless phone, GPS, a PDA device, a telephone or other equipment in a convenient position on a smooth surface such as a windshield of a motor vehicle.

1 Claim, 7 Drawing Sheets






FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7