

US00D593695S

(12) **United States Design Patent**
Levine

(10) **Patent No.:** **US D593,695 S**
(45) **Date of Patent:** **** Jun. 2, 2009**

(54) **LIGHTING DEVICE**

(76) Inventor: **Jonathan E. Levine**, 419 Park Ave.
South, Suite 505, New York, NY (US)
10016

(**) Term: **14 Years**

(21) Appl. No.: **29/327,572**

(22) Filed: **Nov. 7, 2008**

(51) **LOC (9) Cl.** **26-02**

(52) **U.S. Cl.** **D26/42; D26/43**

(58) **Field of Classification Search** D26/37,
D26/42, 46, 49, 43, 44; 362/157, 158, 171,
362/183, 184–188, 194–208

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

D190,295 S *	5/1961	Becker	D26/43
D264,254 S	5/1982	Heritage		
D278,461 S	4/1985	Pepall		
4,977,489 A	12/1990	Fung		
D322,681 S	12/1991	Yuen		
D335,756 S *	5/1993	Gaynor	D26/42
D356,647 S	3/1995	Jung		
D392,760 S	3/1998	Wu		
D403,453 S *	12/1998	Shiau	D26/43
D410,556 S *	6/1999	Yuen	D26/42
D418,238 S *	12/1999	Offiler	D26/42
D438,656 S *	3/2001	Lupica	D26/37
D446,877 S	8/2001	Lester		
D464,162 S	10/2002	Segretto		
D505,217 S *	5/2005	Bayat et al.	D26/42
D528,240 S *	9/2006	Kovacik et al.	D26/42
D538,456 S *	3/2007	Trigiani et al.	D26/42
D540,484 S *	4/2007	Bayat et al.	D26/42
D556,926 S *	12/2007	Thirouin	D26/37
D567,977 S *	4/2008	Jianwei	D26/42
D567,978 S *	4/2008	Jianwei	D26/42
D581,569 S	11/2008	Levine		
D581,571 S	11/2008	Levine		
2006/0050519 A1	3/2006	Lin		

2006/0256584 A1 11/2006 Paoluccio

OTHER PUBLICATIONS

“Koncept Z-Bar LED Lamp,” http://www.konceptech.com/Merchant2/merchant.mv?Screen=PROD&Store_Code=K&Product_Code=LL3001-MBK, visited Jan. 27, 2007, 1 page.

* cited by examiner

Primary Examiner—Adir Aronovich

Assistant Examiner—Carissa C Fitts

(74) *Attorney, Agent, or Firm*—Theodore W. Baker

(57) **CLAIM**

I claim the ornamental design for a lighting device, as shown and described.

DESCRIPTION

FIG. 1 is a perspective view of a lighting device in a collapsed configuration showing my new design, as viewed from the top and one side.

FIG. 2 is a first side elevation view of the lighting device of FIG. 1 in the collapsed configuration.

FIG. 3 is a back elevation view of the lighting device of FIG. 1 in the collapsed configuration.

FIG. 4 is a second side elevation view of the lighting device of FIG. 1 in the collapsed configuration.

FIG. 5 is a front elevation view of the lighting device of FIG. 1 in the collapsed configuration.

FIG. 6 is a top plan view of the lighting device of FIG. 1 in the collapsed configuration.


FIG. 7 is a bottom plan view of the lighting device of FIG. 1 in the collapsed configuration.

FIG. 8 is a bottom plan view of the lighting device of FIG. 1 in the collapsed configuration and with extended base support portions; and,

FIG. 9 is a first side elevation view of the lighting device of FIG. 1 in an expanded position configuration and with an extended hook portion.

The details shown in broken lines illustrate portions of the lighting device that form no part of the claimed design.

1 Claim, 3 Drawing Sheets






FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9