



US00D594381S

(12) **United States Design Patent**
Gurule

(10) **Patent No.:** **US D594,381 S**
(45) **Date of Patent:** **** Jun. 16, 2009**

(54) **SEAT BELT POSITION RETENTION CLIP**

(76) Inventor: **Danny E. Gurule**, 4142 Villa Gomez
La., Stockton, CA (US) 95206

(**) Term: **14 Years**

(21) Appl. No.: **29/310,224**

(22) Filed: **Aug. 1, 2008**

(51) **LOC (9) Cl.** **02-07**

(52) **U.S. Cl.** **D11/212**

(58) **Field of Classification Search** D11/1-2,
D11/200-201, 203-206, 210, 212, 214-219,
D11/222, 224, 226; 24/163 R, 169-171,
24/173, 177-179, 191, 194-195, 197, 200,
24/644, 198

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

- 313,257 A * 3/1885 Thomson 24/69 SK
- D27,688 S * 9/1897 Field D11/200
- D53,302 S * 5/1919 Hausen D11/218
- D55,219 S * 5/1920 Warner et al. D11/210
- 2,066,957 A * 1/1937 Wratschko 24/346
- D113,974 S * 3/1939 Manning D11/218
- D119,153 S * 2/1940 Bowder D11/200
- D133,541 S * 8/1942 Kasen D11/212
- D135,278 S * 3/1943 Zavolner D11/218
- D142,163 S * 8/1945 De Woskin D11/218
- D144,290 S * 4/1946 De Woskin D11/212
- D149,023 S * 3/1948 Rood D11/212
- D171,440 S * 2/1954 Chisholm D11/212
- 2,731,694 A * 1/1956 Steinmetz 24/689
- 3,102,317 A * 9/1963 Cadley 24/664

- D203,438 S * 1/1966 Heimlich D11/210
- 4,160,565 A 7/1979 Matsumoto
- D320,110 S 9/1991 Hawkins
- D322,234 S * 12/1991 Fildan D11/218
- 5,201,099 A 4/1993 Campbell
- D341,712 S 11/1993 Fulcher
- 5,495,646 A 3/1996 Scrutchfield et al.
- 5,692,806 A 12/1997 Jones
- 6,050,647 A 4/2000 Thompson
- D435,807 S * 1/2001 Anscher D11/200
- D439,026 S 3/2001 Reilly
- D450,561 S * 11/2001 Moore et al. D8/349
- 6,390,562 B1 5/2002 Takamizu et al.
- D488,912 S 4/2004 Berger
- D519,404 S 4/2006 Berke et al.
- D568,785 S * 5/2008 Yang et al. D11/218
- D581,314 S * 11/2008 Janz D11/200
- D581,315 S * 11/2008 Paris et al. D11/200

* cited by examiner

Primary Examiner—R. Seifert

(74) *Attorney, Agent, or Firm*—Robert C. Montgomery


(57) **CLAIM**

The ornamental design for a seat belt position retention clip, as shown and described.

DESCRIPTION

FIG. 1 is a perspective view of a seat belt position retention clip, as shown and described;
FIG. 2 is a front view thereof;
FIG. 3 is a rear view thereof;
FIG. 4 is a side view thereof; and,
FIG. 5 is a top view thereof.

1 Claim, 5 Drawing Sheets






Fig. 1




Fig. 2




Fig. 3




Fig. 4




Fig. 5