



US00D596085S

(12) **United States Design Patent**
Bereznai

(10) **Patent No.:** **US D596,085 S**
(45) **Date of Patent:** **** Jul. 14, 2009**

(54) **TWO-PART TELESCOPIC SHOCK
ABSORBER**

(76) Inventor: **Jozsef Bereznai**, Gat u. 8., Budapest
(HU) H-1095

(**) Term: **14 Years**

(21) Appl. No.: **29/276,017**

(22) Filed: **Jan. 11, 2007**

(51) **LOC (9) Cl.** **12-16**

(52) **U.S. Cl.** **D12/159**

(58) **Field of Classification Search** D12/159;
267/64.26, 34; D15/143, 145, 122, 138,
D15/199, 179

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

3,445,103	A *	5/1969	Hennells	267/64.15
3,799,530	A *	3/1974	Stembridge	267/130
3,885,776	A *	5/1975	Blatt	267/34
4,257,499	A *	3/1981	Deschner	188/287
4,284,177	A *	8/1981	Domek	188/280
4,948,103	A *	8/1990	Bowden et al.	267/34
6,126,154	A *	10/2000	Shepherd	267/150
2001/0052441	A1 *	12/2001	Schmidt	188/280

* cited by examiner

Primary Examiner—Louis S Zarfaz

Assistant Examiner—Michael A Pratt

(74) *Attorney, Agent, or Firm*—Birch, Stewart, Kolasch &
Birch, LLP

(57) **CLAIM**

The ornamental design for a two-part telescopic shock absorber, as shown and described.

DESCRIPTION

FIG. 1 is a rear perspective view of a piston serving as a damper or bumper, the piston having an outer body portion with multiple flat attaching flanges arranged one above another;

FIG. 2 illustrates an adjustable rear support having horizontal flanges on an outer side thereof and capable of being mounted at various height positions on the flat attaching flanges of the outer body portion of the piston of FIG. 1;

FIG. 3 is a perspective view showing the adjustable rear support of FIG. 2 attached to a rear side of the piston of FIG. 1;

FIG. 4 is a cut-way view of the adjustable rear support of FIG. 2 attached to the outer body portion on the rear side of the piston of FIG. 1;


FIG. 5 is a perspective view of the adjustable rear support of FIG. 2 and the piston of FIG. 1, the arrow indicating that the adjustable rear support is attached in an upward position;

FIG. 6 is a perspective view of the adjustable rear support of FIG. 2 and the piston of FIG. 1, the arrow indicating that the adjustable rear support is attached in a partially downward position;

FIG. 7 is a perspective view of the adjustable rear support of FIG. 2 and the piston of FIG. 1, the arrow indicating that the adjustable rear support is attached in a further downward position; and,

FIG. 8 is a perspective view showing an adjustable rear support having vertical flanges on an outer side thereof and being attached to a rear side of the piston of FIG. 1.

1 Claim, 4 Drawing Sheets






FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8