



US00D598254S

(12) **United States Design Patent**  
**Alliss**

(10) **Patent No.:** **US D598,254 S**  
(45) **Date of Patent:** **\*\* Aug. 18, 2009**

(54) **TOP UNLOADING TRIMMER HEAD**

- (76) Inventor: **George E. Alliss**, P.O. Box 391,  
Bladenboro, NC (US) 28320
- (\*\*) Term: **14 Years**
- (21) Appl. No.: **29/307,869**
- (22) Filed: **May 15, 2008**

**Related U.S. Application Data**

- (63) Continuation-in-part of application No. 11/811,172,  
filed on Jun. 8, 2007, and a continuation-in-part of  
application No. 12/151,064, filed on May 1, 2008.

- (51) **LOC (9) Cl.** ..... **08-01**  
(52) **U.S. Cl.** ..... **D8/8**  
(58) **Field of Classification Search** ..... D8/8,  
D8/9; 12/56.7, 295; 30/276  
See application file for complete search history.

(56) **References Cited**

**U.S. PATENT DOCUMENTS**

D254,173	S	*	2/1980	Proulx	.....	D8/8
D273,169	S	*	3/1984	Rahe et al.	.....	D8/8
D298,905	S	*	12/1988	Petherick et al.	.....	D8/8
D302,779	S	*	8/1989	Baba	.....	D8/8
D346,727	S	*	5/1994	Eriksson	.....	D8/8
D399,104	S	*	10/1998	Sutliff et al.	.....	D8/8
D460,904	S	*	7/2002	Riley et al.	.....	D8/8
D479,961	S	*	9/2003	Iacona	.....	D8/8
D482,581	S	*	11/2003	Nystrom	.....	D8/8
D482,941	S	*	12/2003	Nystrom	.....	D8/8
D502,368	S	*	3/2005	Nystrom et al.	.....	D8/8
D532,263	S	*	11/2006	Iacona	.....	D8/8
D560,107	S	*	1/2008	Grey	.....	D8/8

\* cited by examiner

*Primary Examiner*—Holly H Baynham

*Assistant Examiner*—Sheryl Lane

(74) *Attorney, Agent, or Firm*—David Lewis

(57) **CLAIM**

The ornamental design for a top unloading trimmer head, as  
shown and described above.

**DESCRIPTION**

The top unloading trimmer head may be used with a vegeta-  
tion trimming device to trim vegetation. The top unloading  
trimmer head attaches to a drive shaft of a vegetation trimmer  
at the collar at the top of the trimmer head. Trimmer line is  
loaded into the trapezoidal shaped openings on the side and  
removed by pulling the trimmer line out through the circular  
openings in the conical portion of the trimmer head.

FIG. 1 is a perspective view of top unloading trimmer head.

FIG. 2 is a front elevational view of the top unloading trimmer  
head of FIG. 1, the back elevational view has the same image  
as the front elevational view.


FIG. 3 is a right side elevational view of the top unloading  
trimmer head of FIG. 1, the left side elevational view has the  
same image of the right side elevational view.

FIG. 4 is a top plan view of the top unloading trimmer head of  
FIG. 1; and,

FIG. 5 is a bottom plan view of the top unloading trimmer  
head of FIG. 1.

The screws (visible in FIGS. 1–4) are drawn using broken  
lines to indicate that the screws are not part of the claimed  
design, but is part of the environment. The bottom cylindrical  
portion (visible in FIGS. 1–3 and 5) is also drawn using  
broken lines to indicate that the bottom cylindrical portion is  
not part of the claimed design, but is part of the environment.  
The broken lines inside the two circular holes that are on the  
top of the trimmer head and are under the arrows (both of the  
holes are visible in FIGS. 1 and 4 and one of the two holes is  
visible in each of FIGS. 2 and 3) are a border indicating a  
region that is not part of the claimed design. The broken lines  
inside the trapezoidal opening on the periphery of the side of  
top unloading trimmer line (seen easiest in FIG. 1, but also  
visible in FIG. 2) represent bounds of the claimed design, and  
the broken line and the region enclosed by the broken lines is  
not part of the claimed design. The broken lines within the  
hole in the opening within the collar at the top of the top  
unloading trimmer (seen best in FIG. 4, but also visible in  
FIG. 1) represent bounds of the claimed design, and the  
broken line and the region enclosed by the broken lines is not  
part of the claimed design.

**1 Claim, 5 Drawing Sheets**






FIG. 1




FIG. 2




FIG. 3






FIG. 4




FIG. 5