

US00D598370S

(12) **United States Design Patent**
Beha

(10) **Patent No.:** **US D598,370 S**
(45) **Date of Patent:** **** Aug. 18, 2009**

(54) **TIRE**

(75) Inventor: **Daniel Ray Beha**, Akron, OH (US)

(73) Assignee: **The Goodyear Tire & Rubber Company**, Akron, OH (US)

(**) Term: **14 Years**

(21) Appl. No.: **29/327,166**

(22) Filed: **Oct. 31, 2008**

(51) **LOC (9) Cl.** **12-15**

(52) **U.S. Cl.** **D12/602; D12/583**

(58) **Field of Classification Search** D12/547-555,
D12/579, 582-591, 596-597, 600-603, 900-901;
152/209.1, 209.8-209.18, 209.25-209.28,
152/455

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

D336,065 S *	6/1993	Patel	D12/602
D351,818 S *	10/1994	Pierot et al.	D12/602
D370,439 S	6/1996	Feider et al.	D12/141
D384,011 S *	9/1997	Kawamata et al.	D12/597
D384,620 S	10/1997	Gillard et al.	D12/147
D385,520 S *	10/1997	Scheuren et al.	D12/602
D388,033 S	12/1997	Scheuren et al.	D12/146
D389,102 S *	1/1998	Gillard et al.	D12/596
D395,414 S *	6/1998	Grosskopf et al.	D12/602
D409,122 S *	5/1999	Kemp et al.	D12/602
D410,420 S	6/1999	de Barys	D12/147
D420,956 S *	2/2000	Rodicq et al.	D12/602
D425,457 S	5/2000	Gillard et al.	D12/146
D425,830 S *	5/2000	Young	D12/602
D427,552 S *	7/2000	Young	D12/602
D427,954 S *	7/2000	De Coninck	D12/602
D444,432 S *	7/2001	Warchol	D12/602
D444,740 S *	7/2001	Le et al.	D12/602
D478,862 S *	8/2003	Gillard et al.	D12/602
D493,415 S *	7/2004	Noailly	D12/579
D499,067 S *	11/2004	Wage	D12/583
D500,010 S	12/2004	Maziarka et al.	D12/590
D501,446 S *	2/2005	Wage	D12/583
D502,683 S *	3/2005	Pang et al.	D12/602
D512,684 S *	12/2005	Robert	D12/602

D514,504 S *	2/2006	Robert	D12/602
D516,015 S *	2/2006	Ikeda	D12/602
D517,472 S	3/2006	Allison	D12/602
D534,117 S	12/2006	Welbes et al.	D12/584
D548,174 S *	8/2007	Souchet	D12/602
D559,773 S *	1/2008	Campana et al.	D12/579
D570,767 S *	6/2008	Miyazaki et al.	D12/579

* cited by examiner

Primary Examiner—Stacia Cadmus

(74) *Attorney, Agent, or Firm*—Richard B. O’Planick

(57) **CLAIM**

The ornamental design for a tire, as shown and described.

DESCRIPTION

FIG. 1 is a perspective view of a tire showing my new design, it being understood that the pattern repeats uniformly throughout the circumference of the tread;

FIG. 2 is a front elevational view thereof;

FIG. 3 is a right side elevational view thereof; the opposite side elevational view being identical thereto;

FIG. 4 is an enlarged fragmentary front elevational view thereof;



FIG. 5 is a perspective view of a second embodiment of a tire showing my new design, it being understood that the pattern repeats uniformly throughout the circumference of the tread and that the opposite side perspective view is identical thereto; and,

FIG. 6 is a front elevational view of a second embodiment, it being understood that an enlarged fragmentary view thereof would be substantially identical to that shown in FIG. 4, with the exception of the inclusion of the sidewall in solid lines.

In the drawings, the broken line showing of the sidewall, inner bead and the peripheral boundary between the tire tread and the sidewall in FIGS. 1 through 4 depict environmental subject matter and form no part of the claimed design.

The dark stippled surface shading represents the recessed portion of the tread grooves having a depth as best shown in FIG. 2.

1 Claim, 6 Drawing Sheets






FIG-1




FIG-2




FIG-3




FIG-4




FIG-5




FIG-6